

JBR Series 30 and 60 Amp Series Switched Receptacles

Dead Front Interlocked Construction


30 and 60 Amp, 600 Vac, 50-400 Hz

Class I, Division 1 and 2, Groups B, C, D

Class II, Division 1 and 2, Groups F, G

Class III

NEMA 3•, 3R•, 4▼, 4X▼, 7BCD, 9FG

	Amp	Hub Size (Inches) ‡	Wire/Poles	Terminal Block Wire Range	Receptacle Catalog Number	Mating Plug Powertite®	Complete Plug
	30	1-1/2	2W, 3P	#10 - #4	JBR3023-150	ACP3023BC	CPH3023B
		1-1/2	3W, 4P	CU-AL	JBR3034-150	ACP3034BC	CPH3034B
	60	1-1/2	2W, 3P	#4 - #6	JBR6023-150	ACP6023BC	CPH6023BC
		1-1/2	3W, 4P	CU-AL	JBR6034-150	ACP6034BC	CPH6034BC

Accessories and Replacement Parts

Description	Catalog Number
Type 4X Drain (field installed)	ECD50B4X
Type 4X Breather (field installed)	BRTB4X
30 Amp Plug Clamping Ring (standard with 30 Amp models)	30CRING
30 Amp Screw Cover (for receptacle)	30SCAP

Maximum Horsepower Ratings of Switch

Phase Motor	Amp	Motor Horsepower		
		240 Vac	480 Vac	600 Vac
1-Phase, 2W, 3P	30	7.5	15	20
	60	10	15	20
3-Phase, 3W, 4P	30	7.5	15	20
	60	10	25	30

• Flip cover suitable for NEMA 3, 3R only.

▼ NEMA 4 rating maintained with Appleton NEMA 4 plug installed. Select screw cover for 4, 4X. Both covers are included with product.

‡ Supplied with (2) 1-1/2" to 1-1/4" reducing bushings.