



## Threaded Rigid Conduit and IMC Nipples and Enlargers

Catalog No.	Size (In.)	Dimensions in Inches			Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
		A	B	C			
<b>Offset Nipples- Malleable Iron</b>							
OFN-50	1/2	1-5/8	7/16	3/4	23.0	25	100
OFN-75	3/4	1-5/8	7/16	3/4	31.0	25	100
OFN-100	1	1-5/8	1/2	3/4	44.0	10	50
OFN-125	1-1/4	1-5/8	9/16	3/4	60.0	5	25
OFN-150	1-1/2	1-5/8	5/8	3/4	82.0	5	25
OFN-200	2	1-5/8	3/4	3/4	112.0	2	10



<b>Bushed Nipples</b>							
CN-38†	3/8	3/8	1/8	15/16	3.0	50	100
CN-50	1/2	7/16	1/8	1	3.4	50	500
CN-75	3/4	1/2	1/8	1-1/4	4.4	50	500
CN-100	1	5/8	1/8	1-1/2	8.5	25	100
CN-125	1-1/4	11/16	1/4	2-1/8	22.0	25	200
CN-150	1-1/2	7/8	1/4	2-3/8	28.5	25	200
CN-200	2	15/16	3/8	2-7/8	48.0	10	100
CN-250	2-1/2	1-1/8	3/8	3-9/16	77.0	5	25
CN-300	3	1-3/16	3/8	4-5/16	114.0	5	25
CN-350	3-1/2	1-1/4	3/8	4-9/16	136.0	5	25
CN-400	4	1-1/4	3/8	5-1/8	169.0	1	5
CN-500	5	1-1/4	7/16	6-5/16	314.0	1	5
CN-600	6	1-5/16	7/16	7-1/2	320.0	1	5




1/2" - 1"  
Pressure Cast  
1 1/4" - 6"  
Malleable Iron

<b>Bushed Nipples- Insulated</b>							
CN-50†	1/2	7/16	1/8	1	3.3	50	500
CN-75†	3/4	1/2	1/8	1-1/4	3.8	50	500
CN-100†	1	5/8	1/8	1-1/2	7.2	25	100
CN-125†	1-1/4	11/16	1/4	2-1/8	20.0	25	200
CN-150†	1-1/2	7/8	1/4	2-3/8	25.0	25	200
CN-200†	2	15/16	3/8	2-7/8	44.0	10	100
CN-250†	2-1/2	1-1/8	3/8	3-9/16	74.0	5	25
CN-300†	3	1-3/16	3/8	4-5/16	112.0	5	25
CN-350†	3-1/2	1-1/4	3/8	4-9/16	124.0	5	25
CN-400†	4	1-1/4	3/8	5-1/8	160.0	1	5
CN-500†	5	1-1/4	7/16	6-5/16	350.0	1	5
CN-600†	6	1-5/16	7/16	7-1/2	360.0	1	5



1/2" - 1"  
Pressure Cast  
1 1/4" - 6"  
Malleable Iron

<b>Male Enlargers††</b>							
ME50-75†	3/4F x 1/2M	9/16	25/32	1-3/8	16.0	25	250
ME75-100†	1F x 3/4M	1/2	15/16	1-3/4	26.0	25	250
ME100-125†	1-1/4F x 1M	9/16	1-1/16	2-1/4	47.0	25	100
ME50-75EP*	3/4F x 1/2M	5/8	15/16	1-3/16	16.0	25	250
ME75-100EP*	1F x 3/4M	11/16	1-1/16	1-7/16	26.0	25	250
ME100-125EP*	1-1/4F x 1M	13/16	1-1/8	1-13/16	47.0	25	250



Steel  
Malleable Iron†

\*Listed for Class I, Div. 1 and 2, Groups A, B, C, D; Class II, Div. 1 and 2, Groups E, F, G.


### Threaded Bell Reducing Couplings- See Section I for an expanded offering.



† Not UL Listed.

†† Not CSA Certified.

Class I, Groups A♦,B,C,D  
 Class II, Groups E,F,G  
 Class III




# CF-2

## Threaded Rigid Conduit and IMC Reducers



Catalog No.	Size (In.)	Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
<b>Reducing Bushings- Steel</b>				
RB50-13♦	1/2 — 1/8	1.5	50	500
RB50-25♦	1/2 — 1/4	2.0	50	500
RB50-38♦	1/2 — 3/8	2.7	100	500
RB75-50♦	3/4 — 1/2	6.0	50	500
RB100-50♦	1 — 1/2	13.8	25	250
RB100-75♦	1 — 3/4	8.0	25	100
RB125-50	1-1/4 — 1/2	29.0	25	100
RB125-75	1-1/4 — 3/4	23.0	25	100
RB125-100	1-1/4 — 1	17.0	25	100
RB150-50	1-1/2 — 1/2	39.0	25	50
RB150-75	1-1/2 — 3/4	35.0	25	50
RB150-100	1-1/2 — 1	31.0	25	50
RB150-125	1-1/2 — 1-1/4	16.5	25	100
RB200-50	2 — 1/2	68.0	5	50
RB200-75	2 — 3/4	64.0	5	25
RB200-100	2 — 1	57.0	5	25
RB200-125	2 — 1-1/4	45.0	5	50
RB200-150	2 — 1-1/2	38.0	5	50



<b>Reducing Bushings- Malleable Iron</b>				
RB250-100	2-1/2 — 1	75.0	5	25
RB250-125	2-1/2 — 1-1/4	78.0	5	25
RB250-150	2-1/2 — 1-1/2	82.0	5	25
RB250-200	2-1/2 — 2	56.0	5	25
RB300-100	3 — 1	130.0	5	25
RB300-125	3 — 1-1/4	135.0	5	25
RB300-150	3 — 1-1/2	142.0	5	25
RB300-200	3 — 2	126.0	5	25
RB300-250	3 — 2-1/2	83.0	5	25
RB350-200	3-1/2 — 2	155.0	5	25
RB350-250	3-1/2 — 2-1/2	164.0	5	25
RB350-300	3-1/2 — 3	92.0	5	25
RB400-200	4 — 2	165.0	2	10
RB400-250	4 — 2-1/2	245.0	2	10
RB400-300	4 — 3	174.0	2	10
RB400-350	4 — 3-1/2	106.0	2	10
RB500-350†	5 — 3-1/2	180.0	1	5
RB500-400†	5 — 4	190.0	1	5
RB600-400†	6 — 4	192.0	1	5
RB600-500†	6 — 5	195.0	1	5


\* UL Recognized.

♦ Suitable for Class I, Group A in addition to Class I Groups B, C, D; Class II, Groups E, F, G; and Class III.

† Class I, Groups C,D; Class II, Groups E,F,G; Class III.

## Threaded Rigid Conduit and IMC Reducers

CF



Aluminum  
RB50-13A – RB600-500A

Catalog No.	Size (In.)	Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
<b>Reducing Bushings– Aluminum</b>				
RB50-13A <sup>◆</sup>	1/2 — 1/8	0.5	50	500
RB50-25A <sup>◆</sup>	1/2 — 1/4	0.7	50	500
RB50-38A <sup>◆</sup>	1/2 — 3/8	0.9	100	500
RB75-50A <sup>◆</sup>	3/4 — 1/2	2.3	50	500
RB100-50A <sup>◆</sup>	1 — 1/2	6.8	25	250
RB100-75A <sup>◆</sup>	1 — 3/4	3.5	25	100
RB125-50A	1-1/4 — 1/2	9.2	25	100
RB125-75A	1-1/4 — 3/4	7.3	25	100
RB125-100A	1-1/4 — 1	6.0	25	100
RB150-50A	1-1/2 — 1/2	14.2	25	50
RB150-75A	1-1/2 — 3/4	12.8	25	50
RB150-100A	1-1/2 — 1	12.0	25	50
RB150-125A	1-1/2 — 1-1/4	6.5	25	100
RB200-50A	2 — 1/2	29.0	5	50
RB200-75A	2 — 3/4	26.5	5	25
RB200-100A	2 — 1	23.6	5	25
RB200-125A	2 — 1-1/4	18.7	5	50
RB200-150A	2 — 1-1/2	16.0	5	50
RB250-100A	2-1/2 — 1	27.0	5	25
RB250-125A	2-1/2 — 1-1/4	28.1	5	25
RB250-150A	2-1/2 — 1-1/2	82.0	5	25
RB250-200A	2-1/2 — 2	20.0	5	25
RB300-100A	3 — 1	46.8	5	25
RB300-125A	3 — 1-1/4	48.6	5	25
RB300-150A	3 — 1-1/2	51.1	5	25
RB300-200A	3 — 2	51.0	5	25
RB300-250A	3 — 2-1/2	35.0	5	25
RB350-200A	3-1/2 — 2	55.8	5	25
RB350-250A	3-1/2 — 2-1/2	57.4	5	25
RB350-300A	3-1/2 — 3	42.0	5	25
RB400-200A	4 — 2	59.4	2	10
RB400-250A	4 — 2-1/2	60.9	2	10
RB400-300A	4 — 3	77.5	2	10
RB400-350A	4 — 3-1/2	50.0	2	10
RB500-350A <sup>†</sup>	5 — 3-1/2	64.8	1	5
RB500-400A <sup>†</sup>	5 — 4	68.4	1	5
RB600-400A <sup>†</sup>	6 — 4	69.1	1	5
RB600-500A <sup>†</sup>	6 — 5	70.2	1	5

\* UL Recognized.

◆ Suitable for Class I, Group A in addition to Class I Groups B, C, D; Class II, Groups E, F, G; and Class III.

† Class I, Groups C, D; Class II, Groups E, F, G; Class III.