





0B/SB-1

4" Square Box Extension Rings and Thru-Ring


With Conduit Knockouts




4SE-1/2
Extension Ring
1-1/2" Deep, Drawn
Top: Two 8-32 screws
Bottom: Two slide-on slots



4SE-3/4
Extension Ring
1-1/2" Deep, Drawn
Top: Two 8-32 screws
Bottom: Two slide-on slots



4SSBE-SPL
Extension Ring
1-1/2" Deep, Welded
Top: Two 8-32 screws
Bottom: Cutout for switch
or handy box




4SES
Combo Extension-Thru-Ring
1-1/2" Deep, Drawn
Top: Two 8-32 screws
Bottom: Two 8-32 screws
and two slide-on slots

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Type Clamp	Knockout Sides	Description Ends	Description Bottom	Wt. Lbs. Per 100	Std. Pkg.
4SE-1/2	1-1/2	21.0	--	(12)1/2"	--	--	44.0	50
4SE-3/4 (53151-3/4)	1-1/2	21.0	--	(8)3/4"	--	--	44.0	50
4SSBE-SPL	1-1/2	21.0	--	(8)1/2" (4)3/4"	--	--	64.0	50
4SES (53151-1/2)	1-1/2	21.0	--	(6)1/2" (4)3/4"	--	--	47.0	50


4" Square Covers

Raised Surface Covers


Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Description	WT. Lbs. Per 100	Std. Pkg.
8360	1/2	8.0	Blank	45.0	25
8361 (52-1T)	1/2	8.0	One Toggle Switch	44.0	25
8362	1/2	8.0	One GFCI Device	35.0	25
8363	1/2	8.0	One Single Flush Receptacle 1-13/32"D	40.0	25
8364	1/2	8.0	Two Single Flush Receptacles 1-13/32" D	38.0	25




8360
1/2" Raised




8361
1/2" Raised



8362
1/2" Raised



8363
1/2" Raised
1-13/32" Opening



8364
1/2" Raised
1-13/32" Openings