







Threadless Rigid Conduit Connectors and Couplings



Catalog No.	Size (In.)	Dimensions in Inches			Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
		A	B	C			
Compression Connectors- Concrete Tight							
NTC-50	1/2	7/8	3/8	1-5/16	15.0	50	200
NTC-75	3/4	7/8	3/8	1-5/8	23.0	25	200
NTC-100	1	1	5/8	1-7/8	40.0	5	25
NTC-125	1-1/4	1-5/16	5/8	2-5/16	64.0	5	50
NTC-150	1-1/2	1-3/8	5/8	2-11/16	90.0	2	10
NTC-200	2	1-7/16	5/8	3-1/4	153.0	1	5
NTC-250	2-1/2	2-3/8	1	3-5/8	258.0	1	10
NTC-300	3	2-7/8	1	4-1/4	350.0	1	10
NTC-350	3-1/2	2-11/16	1	4-7/8	450.0	1	10
NTC-400	4	2-11/16	1	5-3/8	510.0	1	5
Compression Connectors- Insulated- Concrete Tight							
RNTC-50	1/2	7/8	3/8	1-5/16	14.0	50	200
RNTC-75	3/4	7/8	3/8	1-5/8	22.0	25	200
RNTC-100	1	1	5/8	1-7/8	40.0	5	25
RNTC-125	1-1/4	1-5/16	5/8	2-5/16	64.0	5	50
RNTC-150	1-1/2	1-3/8	5/8	2-11/16	90.0	2	10
RNTC-200	2	1-7/16	5/8	3-1/4	145.0	2	10
Compression Couplings- Concrete Tight							
NTCC-50	1/2	2-1/8	1-5/16	—	25.0	25	100
NTCC-75	3/4	2-5/16	1-5/8	—	35.0	25	100
NTCC-100	1	2-1/2	1-7/8	—	57.0	5	25
NTCC-125	1-1/4	2-7/8	2-5/16	—	91.0	5	25
NTCC-150	1-1/2	3-5/16	2-11/16	—	129.0	5	25
NTCC-200	2	4-1/16	3-1/4	—	273.0	1	10
NTCC-250	2-1/2	5	3-5/8	—	375.0	1	10
NTCC-300	3	5-1/16	4-1/4	—	465.0	1	10
NTCC-350	3-1/2	5-1/4	4-7/8	—	605.0	1	5
NTCC-400	4	5-3/8	5-3/8	—	680.0	1	5
90° Compression Box Connectors- Concrete Tight							
NL90-50L	1/2				25.0	25	100
NL90-75L	3/4				40.0	10	50