

Cord Grips ([View All](#) 181kb PDF)

[Previous](#)

Low-Profile Strain Relief Cord Connectors

Non-metallic. Liquid-tight • Oil-tight. Furnished with sealing ring and locknut.



New!


CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	CORD RANGE	UNIT PKG	STD PKG	DIM A	DIM B	I
LPCG503*	50350	1/2	.100-.300	25	100	1.792	.630	1
LPCG50	80086	1/2	.200-.472	25	100	1.792	.630	1
LPCG507	50354	1/2	.385-.750	25	100	2.178	.517	1
LPCG753*	50760	3/4	.100-.300	10	50	1.963	.570	1
LPCG754	50762	3/4	.200-.472	10	50	1.963	.570	1
LPCG757	36100	3/4	.385-.750	10	50	2.250	.600	1
50LPCGBAG†	55080	1/2	.100-.472	-	500	1.792	.630	1
75LPCGBAG†	55082	3/4	.100-.472	-	500	1.963	.570	1

*LPCG503 and LPCG753: UL not applicable for .100 - .195 diameter wire. Factory installation only. Wire strength will not meet UL's 35 lb. pullout test requirement for the fitting

†Includes UF grommet 14/2 to 12/2. Bags not available in black.

When ordering in black, add suffix "BL" to catalog #.

PATENTED.



Arlington's Low Profile Cord Connector has a unique grommet with gripping fingers. These connectors have the largest cord range in the industry — so there are fewer items to stock. A liquid-tight seal superior pullout resistance is accomplished by just tightening the nut. A sealing ring is furnished to assure a liquid-tight seal when installing in non-threaded openings.