



**IN BOX™  
Replacement  
Covers**

Replacement covers sold separately. Clear is not paintable and white is textured, paintable. UV rated plastic for long outdoor life.

**New!**


CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	DESCRIPTION/COVER COLOR	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
DBVC	77640	Single-Gang, Vertical / Clear	10	10	5.650	3.420	.370
DBVW	77642	Single-Gang, Vertical / White	10	10	5.650	3.420	.370
DBHC	77650	Single-Gang, Horizontal / Clear	10	10	3.420	5.650	.370
DBHW	77652	Single-Gang, Horizontal / White	10	10	3.420	5.650	.370
DBV2C	13009	2-Gang, Vertical / Clear	10	10	5.650	5.410	.370
DBV2W	13010	2-Gang, Vertical / White	10	10	5.650	5.410	.370



DBVC



DBV2W



**Weatherproof  
Box Holder**

Zinc die-cast and non-metallic.




CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D
FS50	61050	1/2	25	25	.380	1.550	1.125	.860
FS75	61075	3/4	25	25	.380	1.550	1.125	.860
NMFS50*	54050	1/2	25	25	.380	1.550	1.125	.860
NMFS75*	54075	3/4	25	25	.380	1.550	1.125	.860

\*UV rated non-metallic body.

**Note:** Can be used as an external means of support to meet the requirements of 2008 NEC Section 314-23.



E161207 LR49636



**Assembly Instructions**

Just screw the box support into the electrical box; the entire assembly is held secure with a 1/2" rigid steel conduit or water pipe.

**Other Uses**

- Stubbing up electrical enclosures above concrete slabs with rigid pipe.
- Suspending electrical boxes with rigid pipe between bar joists.
- Suspending fire alarms (smoke detectors) with rigid pipe between bar joists.
- Can be used for installation of equipment where a rigid pipe can be used for a holding means and a 1/2" knockout is present for attachment.

