

### CLAMPS "SNAP-ON" – STEEL

Light Gauge



Cat. #	Conduit Sizes Rigid	Size of Strap Inside	Unit Qty.	Wt. Lbs. Per 100
566	1/4"	.540	500	2
567BX	3/8"	.675	100	14

### ANTI-SHORT BUSHINGS



FMC Trade Cat. #	Size	Armored Cable Size	Unit Qty.
<b>ASB 0</b>	5/16"	14 - 2, 14 - 3, 12 - 2	100
<b>ASB 1</b>	3/8"	14 - 4, 12 - 3, 6 - 1, 4 - 1	100
<b>ASB 2</b>	7/16"	12 - 4, 10 - 2, 10 - 3, 2 - 1	50
<b>ASB 3</b>	1/2"	10 - 4, 8 - 2, 8 - 3, 1 - 1	50
<b>ASB 4</b>	3/4"	8 - 4, 6 - 4, 6 - 3, 6 - 2, 4 - 3, 4 - 2	50
<b>ASB 5</b>	1"	3 - 1, 2 - 1, 2 - 1 / 0, 1 - 300 MCM, 1 - 350 MCM, 1 - 400 MCM, 1 - 450 MCM, 1 - 500 MCM	25
<b>ASB 6</b>	1 1/4"	4 - 1, 4 - 1 / 0, 4 - 2 / 0, 3 - 1 / 0, 3 - 2 / 0, 3 - 3 / 0, 2 - 2 / 0, 2 - 3 / 0, 2 - 4 / 0, 1 - 600 MCM, 1 - 650 MCM, 1 - 700 MCM, 1 - 750 MCM, 1 - 800 MCM, 1 - 900 MCM	10
<b>ASB 7</b>	1 1/2"	4 - 3 / 0, 4 - 4 / 0, 3 - 4 / 0, 3 - 250 MCM, 3 - 300 MCM, 2 - 250 MCM, 2 - 300 MCM, 2 - 350 MCM, 1 - 1000 MCM	10
<b>ASB 8</b>	2" to 2 1/2"	4 - 250 MCM, 4 - 300 MCM, 4 - 350 MCM, 4 - 400 MCM, 4 - 450 MCM, 4 - 500 MCM, 3 - 350 MCM, 3 - 400 MCM, 3 - 450 MCM, 3 - 500 MCM, 2 - 400 MCM, 2 - 450 MCM, 2 - 500 MCM	10

Bushings are packed in clear poly bags.  
Anti-short bushings have a temperature rating of 90°C