

5kV/8kV - EPR Insulation, PVC Jacket - Single Conductor

EPR Insulation - PVC Jacket
MV-105-133% (5kV) or 100% (8kV)
Shielded - Single Conductor - 5kV & 8kV

Medium Voltage



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Annealed bare copper Compact, Class B stranding

Extruded Strand Shield:

- Extruded thermoset semi-conducting stress control layer over conductor

Category Insulation Description:

- Ethylene Propylene Rubber (EPR), colored to contrast with the black conducting shield layers

Extruded Insulation Shield:

- Thermoset semi-conducting polymeric layer free stripping from insulation

Metallic Shield:

- 5 mils annealed copper tape with an overlap of 25%

Category Jacket Description:

- Flame-retardant, moisture and sunlight resistant Polyvinyl Chloride (PVC)

Applications:

- Suitable for use in wet or dry locations in accordance with NEC
- For use in aerial, direct burial, conduit, open tray, and underground duct installations
- For use in direct burial if installed in a system with a ground conductor that is in close proximity, and conforms with NEC 250.4(A)(5)

Standards:

- National Electric Code (NEC)
- UL 1072
- UL listed as Type MV-105 for use in accordance with NEC
- UL 1685
- IEEE 1202
- OSHA Acceptable

PART NUMBER TABLE									
Part#	Gauge	Stranding	Insulation Diameter Min	Insulation Diameter Max	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')	
MVE20601	6	7	.415"	.490"	0.115	0.06	0.65	294.5	
MVE20401	4	7	.455"	.535"	0.115	0.06	0.7	365.4	
MVE20201	2	7	.510"	.590"	0.115	0.06	0.76	467.9	
MVE21/001	1/0	19	.580"	.655"	0.115	0.06	0.82	620.1	
MVE22/001	2/0	19	.620"	.695"	0.115	0.06	0.86	721.5	
MVE23/001	3/0	19	.665"	.745"	0.115	0.08	0.94	877.8	
MVE24/001	4/0	19	.720"	.795"	0.115	0.08	1	1038.2	
MVE225001	250	37	.770"	.850"	0.115	0.08	1.05	1182.3	
MVE235001	350	37	.970"	.945"	0.115	0.08	1.14	1537.1	
MVE250001	500	37	.990"	1.065"	0.115	0.08	1.27	2024.7	
MVE275001	750	61	1.170"	1.250"	0.115	0.08	1.45	2917.8	
MVE2100001	1000	61	1.320"	1.400"	0.115	0.08	1.6	3765.1	

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
 Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
 Seattle • St. Louis • Tampa • Toronto
 © 2020 Omni Cable LLC