

## 600V - UL Type MC - 4 Conductor

**Aluminum Interlocked Armor**

**90°C - 600 Volt**

**UL Type MC**

**4-Conductor**

**Armored Cable**



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Bare compressed copper Class B stranding per ASTM B3 and B8

### Category Insulation Description:

---

- Flame-retardant Cross-linked Polyethylene (XLPE)

### Category Assembly Description:

---

- Conductors are cabled with suitable fillers and bare copper ground conductor Cable core is covered with binder tape

### Spec Ground:

---

- Annealed bare copper Class B stranding per ASTM B13

### Armor:

---

- Aluminum interlocked armor

### Category Jacket Description:

---

- Flame and sunlight resistant black PVC jacket

**Applications:**

- In all raceways or direct burial In wet or dry locations
- Permitted for use in Class I, Division II and Class II, Division II, and Class III, Division I and II per NEC Article 334

**Standards:**

- UL 1569, UL 44, UL 1581, UL Type MC-600 volts
- NEC Type XHHW-2 conductors
- IEEE 1202
- OSHA Acceptable

<b>PART NUMBER TABLE</b>									
<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Ground Gauge</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Nominal OD over Armor</b>	<b>Nominal OD Overall</b>	<b>Material Weight (Lbs./M')</b>	
Y11204A	12	4	12	0.03	0.05	0.58	0.71	272	
Y11004A	10	4	10	0.03	0.05	0.68	0.77	355	
Y10804A	8	4	10	0.045	0.05	0.81	0.9	494	
Y10604A	6	4	8	0.045	0.05	0.91	1.01	655	
Y10404A	4	4	8	0.045	0.05	1.01	1.13	891	
Y10204A	2	4	6	0.045	0.05	1.15	1.28	1283	
Y10104A	1	4	6	0.055	0.05	1.37	1.41	1584	
Y11/004A	1/0	4	6	0.055	0.05	1.47	1.5	1900	
Y12/004A	2/0	4	6	0.055	0.06	1.57	1.61	2356	
Y13/004A	3/0	4	4	0.055	0.06	1.69	1.78	2916	
Y14/004A	4/0	4	4	0.055	0.06	1.83	1.9	3596	
Y125004A	250	4	4	0.065	0.06	1.99	2.07	4184	
Y135004A	350	4	3	0.065	0.075	2.25	2.32	5628	
Y150004A	500	4	2	0.065	0.075	2.57	2.66	7832	
Y175004A	750	4	1	0.08	0.085	3.09	3.26	11825	

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •**  
**Seattle • St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**