

## Power Limited-Type FPLR-, Non Plenum Rated, Nonshielded – 300 Volt

Power Limited Type FPLR Non Plenum Rated  
Nonshielded - 300 Volt



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Solid Bare copper

### Category Assembly Description:

---

- Conductors cabled together

### Applications:

---

- Fire alarm systems
- Smoke detectors
- Burglar alarms
- Dedicated Fire Protective Circuits

### Category Insulation Description:

---

- Color coded Polyvinyl Chloride

### Category Jacket Description:

---

- Red PVC

### Standards:

---

- UL Listed Type FPLR
- NEC Article 761

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
H41802	18	2	.006"	.014"	.132"	16
H41804-04	18	4	.006"	.014"	.154"	27
H41804	18	4	.006"	.014"	.154"	27
H41804-08	18	4	.006"	.014"	.154"	27
H41806	18	6	.006"	.019"	.194"	40
H41808	18	8	.006"	.019"	.210"	67
H41602	16	2	.007"	.014"	.158"	22
H41604	16	4	.007"	.014"	.185"	40
H41402-05	14	2	.010"	.017"	.202"	35
H41402	14	2	.010"	.017"	.202"	35
H41404	14	4	.010"	.017"	.237"	66
H41202	12	2	.010"	.017"	.236"	53

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances. \*H41402-05 has a jacket color of Blue. \*H41804-04 has a jacket color of Green. \*H41804-08 has a jacket color of Yellow.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**