


**EMT COMPRESSION COUPLINGS**

Compression Couplings, Steel

**B06**

Catalog #: 2925US

**APPLICATIONS**

For use in dry locations to couple two ends of EMT conduit  
 RACO Compression couplings are suitable for applications above 600V

**PRODUCT FEATURES**

RACO Steel compression couplings provide concrete-tight connections  
 All steel construction ensures mechanical protection for the raceway  
 All components are zinc electroplated for corrosion protection  
 UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation.

**CULUS**

Standard 514B, UL Listed E195970, C22.2 No. 18

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings,January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf)

**GENERAL PRODUCT INFORMATION**

Trade Size: 1-1/4 in.  
 Country of Origin: USA

**DRAWING DIMENSIONS**

Dimension A: 2.50 in.  
 Dimension B: 2.04 in.

**PACKAGING**

Package Type: Carton  
 Std. Pkg.: 5  
 Ship Carton Qty.: 25  
 Product UPC-A Labeled: No  
 Weight (Lbs. Per/C): 30.00  
 Ship Carton Length (in.): 13.88  
 Ship Carton Width (in.): 10.25  
 Ship Carton Height (in.): 7.25  
 Ctn Weight (Lbs.): 13.75  
 UPC Number: 050169570456  
 I2of5: 50050169570451