


[On Line Catalog](#)


BURNDY Catalog Number	KVSU34
UPC Number	781810083307
Description	UNIV OKLIP 400-500/4-500
Status	Active

Web Use
BURNDY Product Line

General

Mechanical Connector, Cable to Cable, Cu/Al: 400-500 kcmil (Run), 4 AWG-500 kcmil (Tap), ASCR: 336.4-397.5 kcmil (Run), 5 AWG-397.5 kcmil (Tap)

Product Description

Conductor(s)

ACSR Compact Tap (Range)	N/A
Aluminum Run Size (Range)	400 kcmil-500 kcmil
AAAC 5005 Tap (Range)	48.69 (7) kcmil-465.4 (19) kcmil
Copper Tap Range	4 AWG-500 kcmil
CopperWeld Solid Run Size (Range)	N/A
Copper Stranded Run (Range)	400 kcmil-500 kcmil
CopperWeld Stranded Tap Size (Range)	N/A
AAAC 6201 Run (Range)	394.5 (19) kcmil-465.4 (19) kcmil
CopperWeld Solid Tap Size (Range)	N/A
ACSR Compact Run (Range)	N/A
Aluminum Tap Size (Range)	4 AWG-500 kcmil
AAAC 5005 Run (Range)	394.5 (19) kcmil-465.4 (19) kcmil
Galvanized Steel Size (Range)	3/4 (19) in
CopperWeld Stranded Run Size (Range)	N/A
AAAC 6201 Tap (Range)	48.69 (7) kcmil-465.4 (19) kcmil

Approvals / Certifications

UL Listed	N
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N

Physical

Installation Torque	375
Type of Plating	Tin - Electro Plated
Plated (Yes or No)	Y
Product Material	Copper Alloy
Documentation	

For further technical assistance, please contact us