

T&B Catalog Number: LH50G
UPC Number: 03448115287
Description: 1/2" NPT non-metallic gray cord grip.

Status: Active

Features

New threads on body prevent skipping, faster installation.

All nylon construction with TPE gland resists salt water, weak acids, gasoline, alcohol, oil, grease and common solvents.

Application

Suitable for NEMA type 4 and 6 enclosures.

Working temperatures: -22° F (-30° C) to 212° F (100° C). For short periods to 302° F (150° C).

General

Material: Non-Metallic
Color: Gray

Dimension Information

Size (NPT): 1/2
Degree of Bend: Straight
Cable/Wire Range-in/(mm): .170 - .470 (4.3 - 11.9)
A-Clearance hole- in/(mm): .875 (22.2)
B-Maximum O.A. height-in/(mm): 1.72 (43.7)
C-Thread length-in/(mm): .62 (15.7)
D-Wrenching nut thickness-in/(mm): .20 (5.1)
E-Wrenching flats-in/(mm): .95 (24.1)

Packaging

T&B Inner Pack: 100
Package in Units: 800
T&B Sold in UOM: Each
T&B Weight Per UOM: 0.03 lbs. Each

Application Support

Carflex Cord Grips Features & Specifications: Available on Website

Cements-Primers & Sealers-Specifications & Applications: Available on Website

Notes

*Note: It is recommended to use the smallest maximum diameter fitting that will suit your application.

Certifications


RoHS Compliance: Yes

Certifications



File Nbr:
E 51579

For further technical assistance, please contact us...



Suggested Clearance Hole For Nonthreaded Mounting