



**T&B Catalog Number:** LT43D-NEW  
**UPC Number:** 03448108787  
**Description:** 1/2" Carflex®; liquidtight non-metallic fitting.

**Status:** Active

### Images

Image\_1\_s7 lt43c\_cl1\_1

### Features

- Non-conductive and non-corrosive.
- Resistant to oil, acid, ozone and alkaline.
- Easy to install.
- Nitrile rubber "O" ring for a liquidtight termination.
- Temperatures up to 225°deg; F (107°deg; C)
- Meets UL standard 514B.

### Application

For use with Carflex®; conduit and Carflex®; X-Flex®; conduit.

### General

Material Non-Metallic

### Dimension Information

Size (inches)	1/2
Degree of Bend	Straight
A (inches)	0.56
B (inches)	0.91
C (inches)	1.62
D (inches)	1.30
E (inches)	1.40

### Packaging

T&B Order Multiple	50
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	0.08 lbs. Each

### Application Support

T&B Sales Drawings	wsd-ac04398
Carflex Features & Applications	Available on Website
Carflex Installation & Technical Information	Available on Website
Cements-Primers & Sealers-Specifications & Applications	Available on Website

### Certifications

RoHS Compliance Yes

### Certifications



File Nbr:  
E 32447

**For further technical assistance, please contact us...**