

T&B Catalog Number: LT43F-NEW
UPC Number: 03448119418
Description: 1" Carflex®; liquidtight non-metallic fitting.



Status: Active

Features

- Non-conductive and non-corrosive.
- Resistant to oil, acid, ozone and alkaline.
- Easy to install.
- Nitrile rubber "O" ring for a liquidtight termination.
- Temperatures up to 225° F (107° C)
- Meets UL standard 514B.

Application

For use with Carflex® conduit and Carflex®; X-Flex® conduit.

General

Material Non-Metallic

Dimension Information

Size (inches)	1
Degree of Bend	Straight
A (inches)	0.70
B (inches)	1.00
C (inches)	2.20
D (inches)	1.90
E (inches)	1.71

Packaging

T&B Order Multiple	25
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	0.19 lbs. Each

Application Support

T&B Sales Drawings	wsd-ac04398
Carflex Features & Applications	Available on Website
Carflex Installation & Technical Information	Available on Website
Cements-Primers & Sealers-Specifications & Applications	Available on Website

Certifications



File Nbr:
E 32447

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com

