











CrimpALL® Interchangeable Die Sets for Insulated Terminal Crimpers

DESCRIPTION		CAT. NO.	CAT. NO..	MANUFACTURERS OR REMARKS
CABLE TYPE	CONNECTION	TOOL WITH DIE	DIE ONLY	
	 Insulated Terminals and Lugs Solid or Stranded Wire, 22-10 AWG (.34 - 6 mm ²)	12-10 (Yellow), 16-14 (Blue), 22-18 (Red), (6-4 / 2.5 - 1.5 / .34 - .75 mm ²)	PA8021 PA1305	PA2035 For Large Professional Terminals (Panduit, T & B, etc.)
	 Insulated Terminals and Lugs Solid or Stranded Wire, 22-12 AWG (.34 - 4 mm ²)	12-10 (Yellow), 16-14 (Blue), 22-18 (Red), (4/1.5 - 2.5 / .34 - .75 mm ²)	PA8022 PA1308	PA2040 For Standard Commercial Terminals (Hardware Store Brands)
	 Insulated Terminals and Lugs Solid or Stranded Wire, 26-14 AWG (.10 - 2.5 mm ²)	16-14 (Blue), 22-18 (Red), 22-26 (Yellow) (1.5 - 2.5 / .34 - .75 / .34 - .10 mm ²)	PA8023 PA1334	PA2029 For Smaller Wire Barrel Terminals



CrimpALL® Interchangeable Die Sets for Non-Insulated Terminal Crimpers

DESCRIPTION		CAT. NO.	CAT. NO..	MANUFACTURERS OR REMARKS
CABLE TYPE	CONNECTION	TOOL WITH DIE	DIE ONLY	
	 Non-Insulated Terminals and Lugs Solid or Stranded Wire, 22-8 AWG (.34 - .10 mm ²)	10-8 / 14-12 / 18-16 / 22-20 (6 - 10 / 2.5 - 4 / .75 - 1.5 / .34 - .50 mm ²)	PA8024 PA1322	PA2031 For Standard Commercial Terminals

CrimpALL® Interchangeable Die Sets for Open Barrel, Box and Terminal Systems

DESCRIPTION		CAT. NO.	CAT. NO..	MANUFACTURERS OR REMARKS
CABLE TYPE	CONNECTION	TOOL WITH DIE	DIE ONLY	
	 Open Barrel Non-Insulated Terminals, Narrow Lugs and Power Contacts Solid or Stranded Wire, 22-10 AWG (.34 - 6 mm ²), F Type*	22-18 / 16-14 / 12-10 (.34 - .75 / 1.5 - 2.5 / 4-6 mm ²)	PA8026 PA1306	PA2033 For Standard Commercial Terminals
	 Open Barrel Non-Insulated Terminals, Wide Lugs and Power Contacts Solid or Stranded Wire, 22-14 AWG (.34 - 2.5 mm ²), F Type*	16-14 / 22-18 (1.5 - 2.5 / .34 - .75 mm ²)	PA8027	PA2096 For Standard Commercial Terminals
	 Open Barrel D-Sub Contact Pins RS-232 Solid or Stranded Wire, 28-20 AWG (.08 - .50 mm ²), F Type*	28-24 / 22-20 (.08 - .2 / .34 - .5 mm ²)	PA8029 PA1359	PA2097 For Standard D-sub Pins Only; not for HD D-sub

CrimpALL® Interchangeable Die Sets for Wire Ferrules

DESCRIPTION		CAT. NO.	CAT. NO..	MANUFACTURERS OR REMARKS
CABLE TYPE	CONNECTION	TOOL WITH DIE	DIE ONLY	
	 Insulated & Non-Insulated Wire Ferrules Solid or Stranded Wire, 22-10 AWG (.34 - 6 mm ²)	22-20 / 18-16 / 14-12 / 10 (.34 - .55 / .75 - 1.5 / 2.5 - 4 / 6 mm ²)	PA8025 PA1360	PA2095 For DIN or US Type Wire Ferrules

Communications

USA

Tel: 800.435.0786
Fax: 800.451.2632

CANADA

Tel: 800.435.0786
Fax: 800.524.2653

INTERNATIONAL

Tel: +1.815.397.7070
Fax: +1.815.397.9247