



## Tray Cable Connectors ServiceDrive® ASD/VFD

*Patented for use with ServiceDrive®  
and ServiceDrive Plus® Cable Systems*

### Description:

Patented connectors are designed exclusively to terminate ASD/VFD cables in control centers, panel boards, junction boxes and motor control enclosures.

### Listings:

Class I - Div 2  
Class II - Div 1 and 2  
CSA Standard: C22.2 #18.98  
NEMA 4  
IP65  
Thread Type: NPT

Part Number	Wire Size	Hub Size	Set Screw Size
CONASDTC14/3	14 AWG 3 COND	3/4"	10/32 X 1/4"
CONASDTC12/3	12 AWG 3 COND	3/4"	10/32 X 1/4"
CONASDTC10/3	10 AWG 3 COND	3/4"	10/32 X 1/4"
CONASDTC8/3	8 AWG 3 COND	3/4"	10/32 X 1/4"
CONASDTC6/3	6 AWG 3 COND	3/4"	10/32 X 1/4"
CONASDTC4/3	4 AWG 3 COND	1 "	1/4-20 X 1/4"
CONASDTC3/3	3 AWG 3 COND	1 "	10/32 X 1/4"
CONASDTC2/3	2 AWG 3 COND	1-1/4"	1/4-20 X 1/4"
CONASDTC1/3	1 AWG 3 COND	1-1/4"	1/4-20 X 1/4"
CONASDTC1/03	1/0 AWG 3 COND	1-1/2"	1/4-20 X 1/4"
CONASDTC2/03	2/0 AWG 3 COND	1-1/2"	1/4-20 X 1/4"
CONASDTC3/03	3/0 AWG 3 COND	1-1/2"	1/4-20 X 1/4"
CONASDTC4/03	4/0 AWG 3 COND	1-1/2"	1/4-20 X 5/16"
CONASDTC250/3	250 Kcmil 3 COND	2"	1/4-20 X 5/16"
CONASDTC300/3	300 Kcmil 3 COND	2"	5/16-18 X 3/8"
CONASDTC350/3	350 Kcmil 3 COND	2"	5/16-18 X 3/8"
CONASDTC400/3	400 Kcmil 3 COND	2"	5/16-18 X 3/8"
CONASDTC500/3	500 Kcmil 3 COND	2-1/2"	5/16-18 X 3/8"
CONASDTC600/3	600 Kcmil 3 COND	2-1/2"	5/16-18 X 3/8"
CONASDTC750/3	750 Kcmil 3 COND	3"	5/16-18 X 3/8"