

## Bussed Gutters

### Bussed Termination Enclosures



R9000C



R9000EE

#### APPLICATION

- For termination of power utility supply cables

#### CONSTRUCTION

- Type 3R construction
- Removable door with sealing provision
- Lift handles enclosure covers
- Line studs, load lugs

#### STANDARDS

- UL 1773 listed

#### FINISH

- ANSI 61 gray acrylic electrocoat finish

#### Underground-Surface Mount

CATALOG NUMBER	AIC RATING	AMPACITY	VOLTAGE	SERVICE TYPE	CONDUCTOR LUG RANGE		DIMENSIONS (INCHES)		
					PHASE & NEUTRAL LINE*	CONDUCTOR LOAD	HEIGHT (H)	WIDTH (W)	DEPTH (D)
R9007A	--	100	600	1Ø or 3Ø, 3W	14 AWG - 2/0 AWG	14 AWG - 2/0 AWG	8	12	4
R9000B	10K	200	600	1Ø or 3Ø, 3W	6 AWG - 250 kcmil	6 AWG - 250 kcmil	26	12	6
R9000BB	10K	200	600	3Ø, 4W	6 AWG - 250 kcmil	6 AWG - 250 kcmil	26	16	6
R9000C	42K	400	600	1Ø or 3Ø, 3W	2 STUDS / Ø	6 AWG - 600 kcmil	44	12	7
R9000CC	42K	400	600	3Ø, 4W	2 STUDS / Ø	6 AWG - 600 kcmil	44	18	7
R9000E	65K	800	600	1Ø or 3Ø, 3W	4 STUDS / Ø	(3) 4 AWG - 600 kcmil	52	18	11
R9000EE	65K	800	600	3Ø, 4W	4 STUDS / Ø	(3) 4 AWG - 600 kcmil	52	26	11
R9000F	65K	1200	600	1Ø or 3Ø, 3W	6 STUDS / Ø	(4) 4 AWG - 600 kcmil	52	24	11
R9000FF	65K	1200	600	3Ø, 4W	6 STUDS / Ø	(4) 4 AWG - 600 kcmil	52	36	11

\* Every 600 kcmil lug will accept (2) 1/0 - 250 kcmil cables.



**R9000CL**

**APPLICATION**

- For termination of power utility supply cables

**CONSTRUCTION**

- Type 3R construction
- Removable door with sealing provision
- Lift handles enclosure covers
- One piece line/load extrusion - no worrisome connections
- Line & load lugs

**STANDARDS**

- UL 1773 listed

**FINISH**

- ANSI 61 gray acrylic electrocoat finish

**Overhead/Underground – Surface Mount**

CATALOG NUMBER	AIC RATING	AMPACITY	VOLTAGE	SERVICE TYPE	CONDUCTOR LUG RANGE		DIMENSIONS (INCHES)		
					PHASE & NEUTRAL LINE*	CONDUCTOR LOAD	HEIGHT (H)	WIDTH (W)	DEPTH (D)
R9000CL	42K	400	600	1Ø or 3Ø, 3W	(1) 4 AWG - 600 kcmil	(2) 1/0 - 250 kcmil	44	12	7
R9000CCL	42K	400	600	3Ø, 4W	(1) 4 AWG - 600 kcmil	(2) 1/0 - 250 kcmil	44	18	7
R9000EL	65K	800	600	1Ø or 3Ø, 3W	(3) 4 AWG - 600 kcmil	(6) 1/0 - 250 kcmil	52	18	11
R9000EEL	65K	800	600	3Ø, 4W	(3) 4 AWG - 600 kcmil	(6) 1/0 - 250 kcmil	52	26	11
R9000FL	65K	1200	600	1Ø or 3Ø, 3W	(4) 4 AWG - 600 kcmil	(8) 1/0 - 250 kcmil	52	24	11
R9000FFL	65K	1200	600	3Ø, 4W	(4) 4 AWG - 600 kcmil	(8) 1/0 - 250 kcmil	52	36	11

\* Every 600 kcmil lug will accept (2) 1/0 - 250 kcmil cables.

