



360

**360****APPLICATION**

- Used primarily in special metering applications involving self-contained or CT metering

**CONSTRUCTION**

- Type 3R construction
- For connected motor loads up to and including 60 Horsepower at 480 volts
- 24H x 14W x 10D
- Hinged viewing window
- Includes brackets for pole mounting
- AW hub provision
- 3/4 inch plywood backboard

**FINISH**

- ANSI 61 gray acrylic electrocoat finish

**STANDARDS**

- Not UL listed



345

**345 & 351****APPLICATION**

- Used primarily in special metering applications involving self-contained "A" base metering or CT metering

**CONSTRUCTION**

- Type 3R construction
- 345: 24H x 18W x 11D
- 351: 30H x 24W x 11D
- Hinged door with padlock provision
- 3/4 inch plywood backboard

**FINISH**

- ANSI 61 gray acrylic electrocoat finish

**STANDARDS**

- Not UL listed



352

### 352 & 353D

**APPLICATION**

- Used primarily in special metering applications involving self-contained or CT metering

**CONSTRUCTION**

- Type 3R construction
- 28H x 28W x 11D
- Door hinged on right with padlock provision at left – 352 only
- Hinged, utility sealable meter window(s): 1 in 352 – 3 in 353D

**FINISH**

- ANSI 61 gray acrylic electrocoat finish

**STANDARDS**

- Not UL listed



420 & 415H

### 420 & 415H

**APPLICATION**

- Used primarily in special metering applications involving CT metering

**CONSTRUCTION**

- Type 3R construction
- 48H x 34W x 13D
- Double-doors with sealable 3-pt latch handle
- 3/4 inch plywood backboard

**FINISH**

- ANSI 61 gray acrylic electrocoat finish

**ACCESSORIES**

- Equipment mounting racks, catalog #415 (33 x 36), 415H (26 x 28)

**STANDARDS**

- Not UL listed



421



422

### 421 & 422

**APPLICATION**

- Used primarily in special metering applications involving CT metering

**CONSTRUCTION**

- Type 3R construction
- 48H x 34W x 13D
- Double-doors with sealable 3-pt latch handle
- Hinged, utility sealable meter window(s): 1 in 421 – 2 in 422
- 3/4 inch plywood backboard

**FINISH**

- ANSI 61 gray acrylic electrocoat finish

**STANDARDS**

- Not UL listed