

CP Rigid/Intermediate Grade Conduit Fittings

- Insulated Throat Grounding Bushings
- Three Piece Conduit Couplings
- Conduit Bushed Nipples

CP Rigid Intermediate

INSULATED THROAT GROUNDING BUSHINGS





Features:

- Resilient plastic liner resists corrosion, chemicals and temperature extremes
- Insuliner - ULTEM1000 rated at 150°C
- 2 Set-screws provided with each fitting, locks bushings in any desired position
- Standard Finish: Zinc Plated

IRON - 150°C RATED





Set Screw Type - Copper Lug - For Copper Grounding Conductors - Threadless

UL File No. E-6225

	Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
	HGLS1C	1/2"	#4 - #14	50	500	12
	HGLS2C	3/4"	#4 - #14	50	250	13
	HGLS3C	1"	#4 - #14	50	250	16
	HGLS4C	1 1/4"	#4 - #14	25	125	19
	HGLS4-10C	1 1/4"	#1/0 - #8	25	125	31
	HGLS5C	1 1/2"	#4 - #14	10	100	21
	HGLS5-10C	1 1/2"	#1/0 - #8	10	100	33
	HGLS6C	2"	#4 - #14	10	50	27
	HGLS6-10C	2"	#1/0 - #8	10	50	39
	HGLS7C	2 1/2"	#1/0 - #8	10	50	60
	HGLS7-30C	2 1/2"	#3/0 - #6	10	50	83
	HGLS7-250C	2 1/2"	250MCM - #6	10	50	92
	HGLS8C	3"	#1/0 - #8	5	25	70
	HGLS8-30C	3"	#3/0 - #6	5	25	92
	HGLS8-250C	3"	250MCM - #6	5	25	100
	HGLS9C	3 1/2"	#3/0 - #6	1	1	105
	HGLS9-250C	3 1/2"	250MCM - #6	1	1	115
	HGLS10C	4"	#3/0 - #6	1	1	100
	HGLS10-250C	4"	250MCM - #6	1	1	130
	HGLS11C	5"	#3/0 - #6	1	1	140
	HGLS11-250C	5"	250MCM - #6	1	1	150
	HGLS12C	6"	#3/0 - #6	1	1	170
	HGLS12-250C	6"	250MCM - #6	1	1	180

Set Screw Type - Aluminum Lug - For Copper Or Aluminum Grounding Conductors - Threadless

UL File No. E-6225

	Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
	HGLS1	1/2"	#4 - #14	50	500	9
	HGLS2	3/4"	#4 - #14	50	250	10
	HGLS3	1"	#4 - #14	50	250	13
	HGLS4	1 1/4"	#4 - #14	25	125	16
	HGLS4-10	1 1/4"	#1/0 - #8	25	125	20
	HGLS5	1 1/2"	#4 - #14	10	100	18
	HGLS5-10	1 1/2"	#1/0 - #8	10	100	22
	HGLS6	2"	#4 - #14	10	50	24
	HGLS6-10	2"	#1/0 - #8	10	50	28
	HGLS7	2 1/2"	#1/0 - #8	10	50	50
	HGLS7-30	2 1/2"	#3/0 - #6	10	50	58
	HGLS7-250	2 1/2"	250MCM - #6	10	50	60
	HGLS8	3"	#1/0 - #8	5	25	58
	HGLS8-30	3"	#3/0 - #6	5	25	67
	HGLS8-250	3"	250MCM - #6	5	25	70
	HGLS9	3 1/2"	#3/0 - #6	1	1	80
	HGLS9-250	3 1/2"	250MCM - #6	1	1	85
	HGLS10	4"	#3/0 - #6	1	1	90
	HGLS10-250	4"	250MCM - #6	1	1	100
	HGLS11	5"	#3/0 - #6	1	1	115
	HGLS11-250	5"	250MCM - #6	1	1	120
	HGLS12	6"	#3/0 - #6	1	1	145
	HGLS12-250	6"	250MCM - #6	1	1	150




THREE PIECE CONDUIT COUPLINGS

Application:

Used to join two lengths of threaded conduit. Couples conduit when conduit can be turned.

MALLEABLE IRON (Concrete Tight)

- Heavy duty casting
 - Standard Finish: Zinc Plated
- UL File No. E-19189

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	190M	1/2"	25	125	23
	191	3/4"	25	100	35
	192	1"	10	50	60
	193	1 1/4"	5	25	91
	194	1 1/2"	5	25	167
	195	2"	5	5	215
	196	2 1/2"	2	10	430
	197	3"	1	5	463
	198	3 1/2"	1	5	655
	199	4"	1	1	800
	188†	5"	1	1	1200
† Not UL Listed	189†	6"	1	1	2100




CONDUIT BUSHED NIPPLES

Use:

- Use thru knockout to connect box to conduit coupling.
- Use with a locknut to connect two boxes side by side or back to back.
- Use with a locknut to connect fixture housing to continuous runs.




MALLEABLE IRON Non-Insulated Threaded NPSM for rigid conduit and IMC

UL File No. E-19189

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	50*	1/2"	50	500	3
	51	3/4"	25	250	8
	52	1"	10	100	13
	53	1 1/4"	10	100	19
	54	1 1/2"	10	50	30
	55	2"	10	50	37
	56	2 1/2"	5	25	68
	57	3"	5	25	92
	58	3 1/2"	1	5	130
	59	4"	1	5	200
* Steel	60†	5"	1	1	350
† Not UL Listed	61†	6"	1	1	425

Insulated

UL File No. E-19189

	Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
	1050*	1/2"	50	500	3
	1051	3/4"	25	250	4
	1052	1"	10	100	11
	1053	1 1/4"	10	100	19
	1054	1 1/2"	10	50	30
	1055	2"	10	50	37
	1056	2 1/2"	5	25	72
	1057	3"	5	25	96
	1058	3 1/2"	1	5	113
	1059	4"	1	5	187
	1060	5"	1	1	350
* Steel	1061	6"	1	1	450