

# TX6500™ Premium Category 6 U/UTP Copper Cable

## specifications

Category 6 cable shall far exceed ANSI/TIA-568-C.2 and ISO 11801 Class E standards. The conductors shall be 23 AWG construction with FEP (CMP) or polyolefin (CMR) insulation. The copper conductors shall be twisted in pairs, separated by an integrated pair divider and shall be covered by a low smoke, flame-retardant (CMP) jacket or a flame-retardant (CMR) jacket.



## technical information

<b>Electrical performance:</b>	Certified channel performance in a 4-connector configuration up to 100 meters and exceeds ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E standards at swept frequencies up to 250 MHz Certified component performance up to 100 meters and exceeds the component requirements of ANSI/TIA-568-C.2 Category 6 and IEC 61156-5 component standards at swept frequencies up to 250 MHz
<b>Standards compliance:</b>	UL Listed CMP-LP (0.5A) for Plenum
<b>Conductors/insulators:</b>	Plenum – 23 AWG bare copper wire covered by FEP insulation Riser – 23 AWG bare copper wire covered by polyolefin insulation
<b>Flame rating:</b>	Plenum – NFPA 262 and CSA FT-6 Riser – UL 1666 and CSA FT-4
<b>PoE compliance:</b>	Meets IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt for PoE applications
<b>Installation tension:</b>	25 lbf. (110 N) maximum
<b>Temperature rating:</b>	Plenum – 32°F to 122°F (0°C to 50°C) during installation -4°F to 194°F (-20°C to 90°C) during operation Riser – 32°F to 122°F (0°C to 50°C) during installation -4°F to 167°F (-20°C to 75°C) during operation
<b>Cable jacket:</b>	Plenum – low smoke, flame-retardant PVC Riser – flame-retardant PVC
<b>Cable diameter:</b>	Plenum – 0.264 in. (6.7mm) nominal Riser – 0.265 in. (6.8mm) nominal
<b>Cable weight:</b>	Plenum – 32 lbs./1000 ft. (14.5 kg/305m) Riser – 30 lbs./1000 ft. (13.6 kg/305m)
<b>Packaging:</b>	1000 ft. (305m), EZ-Brake™ Reel-in-a-Box Packaging tested to ISTA Procedure 1A

## key features and benefits

<b>Third party tested</b>	Cable has been tested as part of the TX6500™ Copper Cabling System by an independent laboratory and complies with the electrical channel requirements of the following standard: ANSI/TIA-568-C.2 Category 6
<b>Guaranteed channel performance above the standards</b>	Industry leading guaranteed channel performance above the TIA/ISO standards with headroom guarantee
<b>Integrated pair divider</b>	Separates pairs for exceptional cable performance
<b>EZ-Brake™ Reel-in-a-Box</b>	Ensures proper performance and provides quick installation
<b>Tested beyond the standards the standard</b>	Cable has been characterized to 600 MHz, 350 MHz above
<b>Extended temperature range</b>	Allows operation in 90°C (194°F) ambient environment providing error-free performance in high-density cabinets and large cable bundles running PoE+ or PoE++ applications
<b>Reduced attenuation</b>	Maximizes the amount of signal that reaches the receiver and increases bandwidth

## applications

TX6500™ U/UTP Copper Cable is a component of the Panduit™ TX6500™ Copper Cabling System. Interoperable and backward compatible, this end-to-end system provides design flexibility to protect network investments well into the future. With certified performance to the ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E standards, this system will support the following applications:

- Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), 1000BASE-T (Gigabit Ethernet), 10GBASE-T (10 Gigabit Ethernet over limited distances as specified in the industry 10GBASE-T standards)

### TX6500™ Category 6 UTP Copper Cabling System

#### TX6500™ Category 6 U/UTP Copper Cable

<b>Plenum:</b>	PUP6504*-UY
<b>Riser:</b>	PUR6504*-UY

#### Mini-Com® TX6™ PLUS UTP Jack Module

<b>Jack module:</b>	CJ688TG**
---------------------	-----------

#### TX6™ PLUS UTP Patch Cords

<b>Foot lengths:</b>	UTPSP3***Y
<b>Meter lengths:</b>	UTPSP1M^Y

#### DP6™ PLUS Angled Punchdown Patch Panels

<b>24-port, 1 RU:</b>	DPA24688TGY
<b>48-port, 2 RU:</b>	DPA48688TGY

#### DP6™ PLUS Flat Punchdown Patch Panels

<b>12-port:</b>	DP12688TGY
<b>24-port, 1 RU:</b>	DP24688TGY
<b>48-port, 2 RU:</b>	DP48688TGY

#### GP6™ PLUS Category 6 Punchdown System

See website ([www.panduit.com](http://www.panduit.com)) or catalog for complete system information.

#### Cable Prep Tools

<b>Wire snipping tool:</b>	CWST
<b>Wire stripping tool:</b>	CJAST

\*To designate color, add suffix BU (Blue), WH (White), YL (Yellow), or IG (Int'l Gray). For additional cable colors, contact customer service

\*\*To designate color, add suffix IW (Off White), EI (Electric Ivory), IG (International Gray), WH (White), BL (Black), OR (Orange), RD (Red), BU (Blue), GR (Green), YL (Yellow), or VL (Violet).

\*\*\*For lengths 1 to 20 feet (increments of one foot) and 25, 30, 35, 40 feet, change the length designation in part number to the desired length. For standard cable colors other than Off White, add suffix BL (Black), BU (Blue), GR (Green), RD (Red), YL (Yellow), OR (Orange), or VL (Violet) before Y at the end of the part number. For example, the part number for a blue 15-foot patch cord is UTPSP15BUY.


^For lengths 1 to 10 meters (increments of one meter) and 0.5, 1.5, 2.5, 15, 20 meters, change the length designation in the part number to the desired length. For standard cable colors other than Off White, add suffix BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange), or VL (Violet) before Y at the end of the part number. For example, the part number for a blue, 5-meter patch cord is UTPSP5MBUY.

# TX6500™ Premium Category 6 U/UTP Copper Cable

## additional specifications

Mechanical Test	
Ultimate Breaking Strength	>90 lbf (400N)
Minimum Bend Radius	4 x cable diameter
Electrical Test	
Nominal Velocity of Propagation (NVP)	CMP – 73% nominal CMR – 70% nominal
Operating Voltage, Maximum	80 V

## cable construction



### WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA  
Markham, Ontario  
cs-cdn@panduit.com  
Phone: 800.777.3300

PANDUIT EUROPE LTD.  
London, UK  
cs-emea@panduit.com  
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.  
Republic of Singapore  
cs-ap@panduit.com  
Phone: 65.6305.7575

PANDUIT JAPAN  
Tokyo, Japan  
cs-japan@panduit.com  
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA  
Guadalajara, Mexico  
cs-la@panduit.com  
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.  
Victoria, Australia  
cs-aus@panduit.com  
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)

For more information

Visit us at [www.panduit.com](http://www.panduit.com)

Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800.777.3300 and reference COSP258

**PANDUIT®**

©2017 Panduit Corp.  
ALL RIGHTS RESERVED.  
COSP258--WW-ENG  
Replaces WW-COSP137  
3/7/2017