


- Fender Washers
- Zinc Plated Steel
- Stainless Steel

Fender Washers are for general purpose applications. Provides a large load bearing surface. Stainless steel resists corrosion.



CAT NO      UPC      SIZE      STD      SLEEVE      MSTR      WT/STD      UNIT

**Zinc Plated Steel | PC4110**

FENW316114	15505	3/16 x 1-1/4"	100	500	3000	1.65#	C
FENW141	15510	1/4 x 1"	100	500	3000	1.00#	C
FENW14114	15515	1/4 x 1-1/4"	100	500	3000	1.62#	C
FENW14112	15520	1/4 x 1-1/2"	100	500	3000	2.37#	C
FENW142	15521	1/4 x 2"	100		3000	5.65#	C
FENW516114	15525	5/16 x 1-1/4"	100	500	3000	2.05#	C
FENW38114	15527	3/8 x 1-1/4"	100	500	3000	2.20#	C
FENW38112	15530	3/8 x 1-1/2"	100		3000	3.08#	C
FENW382	15531	3/8 x 2"	100		3000	5.50#	C
FENW12112	15535	1/2 x 1-1/2"	100		3000	2.75#	C
FENW122	15540	1/2 x 2"	100		3000	5.25#	C
FENWT14114	15536	 1/4 x 1-1/4"	250		1500	5.23#	C
FENWT38114	15537		250		1500	4.58#	C
FENWT12112	15538		150		900	4.01#	C

**Stainless Steel | PC4010**

FENWS3161	69906	3/16 x 1"	100	500	5000	1.19#	C
FENWS141	69908	1/4 x 1"	100	500	5000	1.25#	C
FENWS14114	69910	1/4 x 1-1/4"	100	500	3000	2.09#	C
FENWS14112	69912	1/4 x 1-1/2"	100	500	3000	2.85#	C
FENWS516112	69914	5/16 x 1-1/2"	100	500	3000	2.30#	C
FENWS38112	69916	3/8 x 1-1/2"	100		3000	3.26#	C
FENWS122	69918	1/2 x 2"	100		3000	5.12#	C

**"S" Hooks | PC 4870**

- "S" Hooks
- Zinc Plated Steel

S HOOKS are used to hang fixtures suspended from chain.



CAT NO	UPC	OVERALL LENGTH	DIAMETER	OPENING	INSIDE DIA	STD	MSTR	WT/STD	UNIT
S1	30805	1"	0.120	3/16"	1/4"	100	5000	0.74#	C
S2	30810	1-1/2"	0.177	11/32"	13/32"	100	5000	2.47#	C
S3	30815	2"	0.243	7/16"	9/16"	50	2500	3.01#	C
S4	30820	2-1/2"	0.306	1/2"	3/4"	50	2500	6.04#	C
S5	30825	3"	0.306	5/8"	7/8"	50	2500	7.11#	C