

- Polymers and Butyl Rubber
- Gray
- 100% Solid
- Low Odor
- Temperature Range: -20° F. to 180° F.

- Sound Barrier
- Non Hardening
- Flexible
- Forms Watertight Seal



CAT NO	UPC	SIZE	STD	MSTR	WT/STD	UNIT
68	15250	1/8 x 6 x 8"	100	100	33.80#	C



Insulpads are used on electrical outlet boxes, under moldings, around windows, doors and vents; or wherever metal overlaps metal. It is used to seal nail and knockout holes in boxes and to prevent air transmitted sound. It is heavy mastic which is flexible, and can be pressed into any shape to form a water and airtight seal. It is non hardening and remains pliable as applied or packaged. Insulpads are supplied on a special silicone treated release paper.

Duct Seal | PC 6130

- UL Listed
- Adheres to Most Clean Surfaces
- Non Toxic / Asbestos Free

Duct Seal (Prest "O" Seal) is used to seal around junction box flashings, service masts, etc. It is heavy mastic, which is flexible and can be pressed into any shape to form a water and airtight seal.



CAT NO	UPC	SIZE	STD	MSTR	WT/STD	UNIT
LHD1	17230	1 lb	50	50	50.00#	Ea
LHD5	17235	5 lb	10	10	50.00#	Ea

ABS & PVC Cement | PC 6170

- Virgin PVC Resin
- Clear or Gray
- Reduced Emission VOC
- Pint or Quart

Low VOC (Volatile Organic Compound) ABS & PVC Cement conform to South Coast Air Quality Management District regulations (Rule 1168), and are used for electrical conduits and non pressure applications. All conduit schedules & classes through 6". Joins ABS to PVC, ABS to ABS, PVC to PVC.



CAT NO	UPC	CONTENTS	COLOR	STD	MSTR	WT/STD	UNIT
PV16CL	30950	Pint	Clear	12	12	14.64#	Ea
PV16GR	30955	Pint	Gray	12	12	14.64#	Ea
PV32CL	30960	Quart	Clear	12	12	26.88#	Ea
PV32GR	30965	Quart	Gray	12	12	26.88#	Ea

ABS & PVC Primer | PC 6170

- Thin Solvent
- Purple
- Fast Acting
- Pint

ABS & PVC Primer is a water thin solvent to be used in conjunction with PVC cement to produce the best PVC joint possible. It also acts as a cleaner as well as a pre-softener, and is suitable for use on all types, classes, and schedules of PVC pipes and fittings.



CAT NO	UPC	CONTENTS	COLOR	STD	MSTR	WT/STD	UNIT
PR16	30975	Pint	Purple	12	12	13.56#	Ea

See new products at www.lhdottie.com

UPC Vendor ID Code: 78-1002

