






N-4

Class I, Div. 1 and 2,
Groups B,C,D
Class II, Div. 1 and 2,
Groups E,F,G
Class III
NEMA 7 B CD,9EFG

EDS Factory Sealed Tumbler Switches: Front Operated; Explosionproof, Dust-Ignitionproof

Malleable Iron Body and Cover.
UNILETS® for Use with Threaded Metal Conduit.
Furnished with Internal Ground Screw.

	Hub Size, Inches	Switch	Catalog Number†	
			Dead-End	Feed-Thru
Single Gang				
20-Ampere—120-277 Volt A.C.*				
	1/2	1-Pole	EDS150-F1	EDSC150-F1
	1/2	2-Pole	EDS150-F2	EDSC150-F2
	1/2	3-Way	EDS150-F3W	EDSC150-F3W
	1/2	4-Way	EDS150-F4W	EDSC150-F4W
Dead-End	3/4	1-Pole	EDS175-F1	EDSC175-F1
	3/4	2-Pole	EDS175-F2	EDSC175-F2
	3/4	3-Way	EDS175-F3W	EDSC175F3W
	3/4	4-Way	EDS175-F4W	EDSC175F4W
	1	1-Pole	EDS110-F1	EDSC110-F1
	1	2-Pole	EDS110-F2	EDSC110-F2
	1	3-Way	EDS110-F3W	EDSC110-F3W
	1	4-Way	EDS110-F4W	EDSC110-F4W
30-Ampere—120-277 Volt A.C.**				
	3/4	1-Pole	EDS175-F13	EDSC175-F13
	3/4	2-Pole	EDS175-F23	EDSC175-F23
	3/4	3-Way	EDS175-F3W3	EDSC175-F3W3
Feed-Thru	1	1-Pole	EDS110-F13	EDSC110-F13
	1	2-Pole	EDS110-F23	EDSC110-F23
	1	3-Way	EDS110-F3W3	EDSC110-F3W3
Two Gang				
20-Ampere—120-277 Volt A.C.*				
	1/2	1-Pole	EDS250-F1	EDSC250-F1
	1/2	2-Pole	-----	EDSC250-F2
	1/2	3-Way	-----	EDSC250-F3W
	1/2	4-Way	-----	EDSC250-F4W
Dead-End	3/4	1-Pole	EDS275-F1	EDSC275-F1
	3/4	2-Pole	-----	EDSC275-F2
	3/4	3-Way	EDS275-F3W	EDSC275F3W
	3/4	4-Way	-----	EDSC275F4W
	1	1-Pole	EDS210-F1	EDSC210-F1
	1	2-Pole	EDS210-F2	EDSC210-F2
	1	3-Way	EDS210-F3W	EDSC210-F3W
	1	4-Way	EDS210-F4W	EDSC210-F4W
Feed-Thru				

† For Aluminum Backbox and Cover, add Suffix - A.

* 20 Amp—1 HP at 120 Volt A.C. and 2 HP at 240 Volt A.C. **30 Amp—2 HP at 120 Volt A.C. or 240 Volt A.C.

◊ Shaded area indicates items suitable for Class I, Group B, as well as Class I, Groups C and D; Class II, Groups E,F,G; and Class III.