

# ETP Steel EMT Set Screw Couplings

## 5000S Series Couplings

### Application

- To ground and secure EMT raceway sections together.

### Features

- Heavy steel walls.
- Concretetight when taped.
- Pre-set/pre-staked set screws.
- Three-way combination screws 1/2" thru 1".
- Slotted hexhead screw 1-1/4" thru 4".

### Material/Finish

- Steel/zinc plated

### Certifications and Compliances

- UL Standard: 514B
- UL Listed: (1/2 - 2) E14895, E14815
- UL Listed: (2-1/2 - 4) E11853, E14814
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E14895, E14815
- CSA Certified: 028507
- NEMA: FB-1



5050S — 5100S



5125S — 5400S



5050US - 5200US



5250US - 5400US

Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters		Weight Lbs. / Kgs. Per 100
		Body Length	Maximum Diameter	
1/2	5050S	1.75/44.5	0.84/21.3	10.00/4.54
3/4	5075S	2.13/54.1	1.08/27.4	16.00/7.26
1	5100S	2.50/63.5	1.31/33.3	25.00/11.34
1-1/4	5125S	3.25/82.6	1.69/42.9	45.00/20.41
1-1/2	5150S	3.75/95.3	1.94/49.3	60.00/27.22
2	5200S	4.00/101.6	2.38/60.5	82.00/37.19
2-1/2	5250S	4.25/108.0	3.13/79.5	166.00/75.30
3	5300S	4.50/114.3	3.75/95.3	213.00/96.62
3-1/2	5350S	4.75/120.7	4.25/108.0	260.00/117.93
4	5400S	5.00/127.0	4.75/120.7	300.00/136.08

## 5000US Series Couplings

### Application

- To ground and secure EMT raceway sections together.

### Features

- Made in the U.S.A.
- Heavy steel walls.
- Concretetight when taped.
- Pre-set/pre-staked set screws.
- Three-way combination screws 1/2" thru 2".
- Hexhead screws 2-1/2" thru 4".

### Material/Finish

- Steel/zinc plated

### Certifications and Compliances

- UL Standard: 514B
- UL Listed: (1/2 - 2) E14815
- CSA Standard: C22.2 No. 18.3
- cUL Listed: (1/2 - 2) E14815
- NEMA: FB-1