

## Anti- Short Bushings & Cable Staples

### Type AS

#### Thermoplastic

#### Use:

These anti-short bushings are used in the terminations of flexible metal conduit and armored cables. Inserted into I.D. of each termination point to protect the conductors from the sharp edges of the raceway where cut.



#### Material/Finish:

Plastic

#### Third Party Certification:



CSA Certified: LR24719



Type AS-O

		Dimensions in Inches			
Trade Size (inches)	Catalog Number	A	B	For Cable Sizes	
Bagged (Packed in Printed Polybags)					
$\frac{1}{16}$	AS-0-100	0.57	0.64	14-2, 14-3, 12-2, Armored Cable; 5/169 Flexible Conduit	
$\frac{3}{16}$	AS-1-100	0.67	0.66	14-4, 12-3, 6-1, 4-1, Armored Cable; 3/89 Flexible Conduit	
$\frac{1}{2}$	AS-2-100	0.61	0.82	12-4, 10-2, 10-3, 2-1, Armored Cable; 7/169 Flexible Conduit	
$\frac{3}{4}$	AS-3-50	0.67	0.94	10-4, 8-2, 8-3, 1-1, Armored Cable; 1/29 Flexible Conduit	
$1$	AS-4-50	0.79	1.16	8-4, 6-2, 6-3, Armored Cable; 3/49 Flexible Conduit	

### Type SN

#### Cable Staples

#### Use:



To secure non-metallic sheathed cable and SE/U to wooden structure members per NEC Article 336-15.

#### Material/Finish:

Steel

#### Note:

SN Cable Staples are furnished in plastic containers.



Type SN

Trade Size Quantities (inches)	Catalog Number	Dimensions in Inches			Standard Package	
		A	B	C	Carton	Package
NMC 2-Cond. 12 & 14						
1 x $\frac{1}{2}$	SN-400	0.73	0.13	1.12	100	10,000
1 x $\frac{1}{2}$	SN-405	0.73	0.13	1.12	500	10,000
1 x $\frac{1}{2}$	SN-410	0.73	0.13	1.12	—	15,000
NMC 3-Cond. 10-12 & 14 Wire						
$1\frac{1}{4}$ x 9/16	SN-1000	0.80	0.14	1.37	100	5,000
$1\frac{1}{4}$ x 9/16	SN-1050	0.80	0.14	1.37	500	5,000
$1\frac{1}{4}$ x 9/16	SN-1100	0.80	0.14	1.37	—	10,000
SE/U 3-Cond. No. 6						
$1\frac{1}{8}$ x $\frac{1}{16}$	SN-3000	1.30	0.26	1.32	100	5,000