

# Zinc Liquidtight Connectors

For Liquidtight Flexible Metal Conduit & Type B Non-Metallic Conduit

## Type LMM

### Straight

#### Use:

Terminate and seal liquidtight flexible metal conduit to either oiltight, liquidtight or raintight box or enclosure. Connectors can be used with tapered thread female entry or unthreaded knockout using the provided sealing washer and locknut.

#### Features:

- Furnished with locknut and sealing ring
- Liquidtight/Raintight/Oiltight
- Suitable for grounding (through 1¼")
- Suitable for wet locations

#### Material/Finish:

Zinc Die Cast

#### Third Party Certification:





UL Listed: E-32539



LMM-01 through LMM-61  
LMM-02 through LMM-62  
CSA Certified: LR14489  
LMM-71 through LMM-91  
LMM-72 through LMM-92  
CSA Certified: LR39354

#### Applicable Third Party Standards:

UL Standard: 514B  
CSA Standard: C22.2 No. 18  
NEMA: FB-1  
Fed. Spec: W-F-406D,  
Type 1, Class 3, Style 1



Type LMM-01

Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches		
			A	B	C Dia.
⅜*	LMM-01	LMM-02	1.49	0.53	1.28
½	LMM-11	LMM-12	1.49	0.53	1.28
¾	LMM-21	LMM-22	1.53	0.53	1.56
1	LMM-31	LMM-32	1.95	0.66	1.81
1¼	LMM-41	LMM-42	2.06	0.67	2.25
1½	LMM-51	LMM-52	2.06	0.67	2.50
2	LMM-61	LMM-62	2.04	0.67	3.00
2½	LMM-71	LMM-72	3.54	1.02	3.68
3	LMM-81	LMM-82	4.05	1.07	4.38
3½	LMM-85	LMM-86	4.44	1.09	4.98
4	LMM-91	LMM-92	4.99	1.15	5.54

\*⅜" fits ½" KO