

# 2900C Series Electric Baseboard - Heavy Duty Commercial Convection Heater



Manufactured in U.S.A.



## Features

- Bankers bronze with stainless steel heating element and Aluminum fins.
- Powder coated 22 Gauge steel front with 20 Gauge junction boxes located on each end of the heater - junction boxes contain quick connect cable clamps and 6" ground lead wires.
- Standard inlet and outlet wire guards.
- Over-temperature thermal limit extends entire heated length of unit.
- A full length wireway provided along the back of the heater.
- Heater can be mounted to the wall by using the key hole knockouts every 4" at the back of the heater.
- Optional In-Built thermostats field installed in the junction box.
- HEIGHT: 6" DEPTH: 2-1/2"

## Standard Models

UPC# 686334	BRONZE MODEL	WATTS	BTU's	VOLTS	AMPS	HEATER LENGTH (IN)	WEIGHT (LBS)	LIST
103831	E2903-024C	375	1275	120	3.1	24	5	137
103848	F2903-024C	375	1275	208	1.8			
103855	H2903-024C	375 / 281	1275 / 955	240 / 208	1.6 / 1.4	28	6	171
103862	G2903-024C	375 / 281	1275 / 955	277 / 240	1.6 / 1.2			
103879	E2905-028C	500	1706	120	4.2	36	7	195
103886	F2905-028C	500	1706	208	2.4			
103893	H2905-028C	500 / 375	1706 / 1275	240 / 208	2.1 / 1.8	40	8	204
103909	G2905-028C	500 / 375	1706 / 1275	277 / 240	1.8 / 1.6			
103916	E2906-036C	600	2040	120	5.0	48	10	236
103923	F2906-036C	600	2040	208	2.9			
103930	H2906-036C	600 / 450	2040 / 1530	240 / 208	2.5 / 2.2	60	12	282
103947	G2906-036C	600 / 450	2040 / 1530	277 / 240	2.2 / 1.9			
103954	E2907-040C	750	2550	120	6.3	72	14	324
103961	F2907-040C	750	2550	208	3.6			
103978	H2907-040C	750 / 563	2550 / 1914	240 / 208	3.1 / 2.7	84	16	360
103985	G2907-040C	750 / 563	2550 / 1914	277 / 240	2.7 / 2.6			
103992	E2910-048C	1000	3413	120	8.3	96	18	398
104005	F2910-048C	1000	3413	208	4.8			
104012	H2910-048C	1000 / 750	3413 / 2550	240 / 208	4.2 / 3.6	120	22	418
104029	G2910-048C	1000 / 750	3413 / 2550	277 / 240	3.6 / 3.1			
104036	G2907-048C	750	2550	277	3.4	24	5	137
104043	E2912-060C	1250	4250	120	10.4			
104050	F2912-060C	1250	4250	208	6.0			
104067	H2912-060C	1250 / 938	4250 / 3189	240 / 208	5.2 / 4.5	28	6	171
104074	G2912-060C	1250 / 938	4250 / 3189	277 / 240	4.5 / 3.9			
104081	G2909-060C	938	3189	277	3.4	36	7	195
104098	E2915-072C	1500	5100	120	12.5			
104104	F2915-072C	1500	5100	208	7.2	40	8	204
104111	H2915-072C	1500 / 1125	5100 / 3825	240 / 208	6.3 / 4.7			
104128	G2915-072C	1500 / 1125	5100 / 3825	277 / 240	5.4 / 4.7	48	10	236
104135	G2911-072C	1125	3825	277	4.1			
104142	F2917-084C	1750	5950	208	8.4	60	12	282
104159	H2917-084C	1750 / 1313	5950 / 4464	240 / 208	7.3 / 6.3			
104166	G2917-084C	1750 / 1313	5950 / 4464	277 / 240	6.3 / 5.5	72	14	324
104173	G2913-084C	1313	4464	277	4.7			
104180	F2920-096C	2000	6826	208	9.6	84	16	360
104197	H2920-096C	2000 / 1500	6826 / 5100	240 / 208	8.3 / 7.2			
104203	G2920-096C	2000 / 1500	6826 / 5100	277 / 240	7.2 / 6.3	96	18	398
104210	G2915-096C	1500	5100	277	5.4			
104265	F2925-120C	2500	8532	208	12.0	120	22	418
104272	H2925-120C	2500 / 1875	8532 / 6375	240 / 208	10.4 / 9.0			
104289	G2925-120C	2500 / 1875	8532 / 6375	277 / 240	9.0 / 7.8			
104296	G2918-120C	1875	6375	277	6.8			

## International Models

UPC# 686334	BRONZE MODEL	WATTS	BTU's	VOLTS	AMPS	HEATER LENGTH (IN)	WEIGHT (LBS)	LIST
118057	M2903-024CI	375	1275	220	1.7	24	5	137
118064	H2903-024CI			240	240			
118071	M2905-028CI	500	1706	220	2.3	28	6	171
118088	H2905-028CI			240	2.1			
118095	M2906-036CI	600	2040	220	2.7	36	7	195
118101	H2906-036CI			240	2.5			
118118	M2907-040CI	750	2550	220	3.4	40	8	204
118125	H2907-040CI			240	3.1			
118132	M2910-048CI	1000	3413	220	4.6	48	10	236
118149	H2910-048CI			240	4.2			
118156	M2912-060CI	1250	4250	220	5.7	60	12	282
118163	H2912-060CI			240	5.2			
118170	M2915-072CI	1500	5100	220	6.8	72	14	324
118187	H2915-072CI			240	6.3			
118194	M2917-084CI	1750	5950	220	8.0	84	16	360
118200	H2917-084CI			240	7.3			
118217	M2920-096CI	2000	6826	220	9.1	96	18	398
118224	H2920-096CI			240	8.3			
118231	M2925-120CI	2500	8532	220	11.4	120	22	418
118248	H2925-120CI			240	10.4			