

# DIGITAL CLAMP METERS



FEATURES	CL110	CL210	CL310	CL600	CL700	CL800
Durability						
Drop Protection	3.3 ft. (1 m)	3.3 ft. (1 m)	3.3 ft. (1 m)	6.6 ft. (2 m)	6.6 ft. (2 m)	6.6 ft. (2 m)
Ingress Protection	—	—	—	IP40	IP40	IP40
Safety	CAT III 600V	CAT III 600V	CAT III 600V	CAT IV 600V	CAT IV 600V	CAT IV 600V
AC Voltage (Volts)	600V	600V	600V	1000V	1000V	1000V
DC Voltage (Volts)	600V	600V	600V	1000V	1000V	1000V
AC Current (Amps)	400A	400A	400A	600A	600A	600A
DC Current (Amps)	—	—	—	—	—	600A
Ohms (Resistance)	20MΩ	20MΩ	40MΩ	60MΩ	60MΩ	60MΩ
AC Millivolts	•	•	—	—	—	—
DC Millivolts	•	•	•	•	•	•
True RMS	—	—	•	•	•	•
Audible Continuity	•	•	•	•	•	•
Backlight	•	•	•	•	•	•
Temperature	—	-40° – 1832°F (-40° – 1000°C)	-40° – 1832°F (-40° – 1000°C)	—	-14° – 1000°F (-26° – 538°C)	-14° – 1000°F (-26° – 538°C)
Low Impedance	—	—	—	—	•	•
Non-Contact Voltage Testing	—	—	—	•	•	•
Auto Ranging	•	•	•	•	•	•
Range Hold	•	•	•	•	•	•
Data Hold	•	•	•	•	•	•
Diode Test	—	—	•	•	•	•
Capacitance Test	—	—	4000 μF	—	6000 μF	6000 μF
Frequency / Duty Cycle	—	—	10Hz – 1MHz	—	1Hz – 500 KHz	1Hz – 500 KHz
Max / Min	MAX only	MAX only	•	•	•	•
Magnetic Mount	—	—	—	Available As Accessory	Available As Accessory	Available As Accessory
Worklight	—	—	—	—	—	•
Auto-Power Off	•	•	•	•	•	•
LCD Display Count	2000	2000	4000	6000	6000	6000