



Keeping your world up and running.®

Search



[Products](#)

[Where to Buy](#)

[Solutions](#)

[Training/Education](#)

[Community](#)

[Support](#)

[« Accessories](#)

Fluke TP175 TwistGuard™ Test Probes

The Fluke TP175 TwistGuard® Test Probes have adjustable tip lengths that allow you to work safely in different settings.

Fluke Store

[Manuals](#)



[Write a review](#)



[Overview](#)

[Features](#)

[Reviews](#)

[Specs](#)

[Models/Accessories](#)

[Resources](#)



[Product Registration](#)

Ratings: CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A max., Pollution Degree 2

Exposed probe tip length: 19 mm to 4 mm (0.75 inch to 0.16 inch)

Environmental ratings: -20 °C to 55 °C (-4 °F to 131 °F), altitude: 2000 m (6,562 ft)

TL175 and TL175E also available. TL175E includes removable 4 mm lantern tips that thread onto the lead tip.

Products

[Buy Fluke Accessories](#)
[Buy Factory Reconditioned](#)
[Contests and Promotions](#)
[Manuals](#)
[New From Fluke](#)
[Product Registration](#)
[Test Tools Catalog](#)
[Where to Buy](#)

Company

[About Us](#)
[Awards](#)
[Careers](#)
[Companies](#)
[Compliance](#)
[Press](#)
[Supplier Handbook](#)
[Tax Information](#)

Customer Service

[Contact Us](#)
[Directions](#)
[Feedback](#)
[Safety Notices](#)

**Fluke Newsletters
Signup**

