







Covers and Gaskets for Form 85® Unilet® Conduit Outlet Bodies and Wiring Capacity

Covers Furnished with Stainless Steel Fastening Screws.

FITTINGS: CONDUIT BODIES

Covers and Gaskets

Body Size (Inches)	Blank Stamped Aluminum ‡	Blank Cast Aluminum	Neoprene	Composition Fiber
	 Domed: 1/2" – 3"	 Flat: 1/2" – 2"		
	 Flat: 3-1/2" – 6"	 Domed: 2-1/2" – 4"	Tear out inner section to convert to "open type" gasket.	
1/2	K50-A	K50-CA	GK50-N	GK50-V
3/4	K75-A	K75-CA	GK75-N	GK75-V
1	K100-A	K100-CA	GK100-N	GK100-V
1-1/4	K125 & 150-A	K125 & 150-CA	GK125-150-N	GK125-150-V
1-1/2	K125 & 150-A	K125 & 150-CA	GK125-150-N	GK125-150-V
2	K200-A	K200-CA	GK200-N	GK200-V
2-1/2	K250 & 300-A	K250 & 300-CA	GK250-300-N	GK-250-300-V
3	K250 & 300-A	K250 & 300-CA	GK250-300-N	GK-250-300-V
3-1/2	K350 & 400-A	K350 & 400-CA	GK350-400-N	GK-350-400-V
4	K350 & 400-A	K350 & 400-CA	GK350-400-N	GK-350-400-V

Wiring Capacity: Combine Body and Cover Capacities for Total Usable Capacity per NEC 314.16(A)

Hub Size (Inches)	Capacity (in ³ /dm ³)										
	C	E	LB	LL LR	LRL	T	TA	TB	X	Stamped Cover	Cast Cover
1/2	4.00/ 0.07	4.00/ 0.07	4.00/ 0.07	4.00/ 0.07	—	4.00/ 0.07	—	6.00/ 0.10	4.00/ 0.07	0.50/ 0.01	0.00/ 0.00
3/4	7.00/ 0.11	7.00/ 0.11	7.00/ 0.11	7.00/ 0.11	—	7.00/ 0.11	—	7.00/ 0.11	7.00/ 0.11	0.80/ 0.01	0.30/ 0.00
1	11.80/ 0.19	11.80/ 0.19	11.80/ 0.19	11.80/ 0.19	—	11.80/ 0.19	—	13.00/ 0.21	11.80/ 0.19	1.00/ 25.4	0.50/ 0.01
1-1/4	34.80/ 0.57	—	34.80/ 0.57	34.80/ 0.57	—	34.80/ 0.57	—	35.00/ 0.57	—	2.50/ 0.04	0.80/ 0.01
1-1/2	35.00/ 0.57	—	35.00/ 0.57	35.00/ 0.57	—	35.00/ 0.57	—	34.50/ 0.57	—	2.50/ 0.04	0.80/ 0.01
2	70.00/ 1.15	—	70.00/ 1.15	70.00/ 1.15	—	70.00/ 1.15	—	71.00/ 1.16	—	6.50/ 0.11	1.00/ 0.02
2-1/2	143.00/ 2.34	—	139.00/ 2.28	140.50/ 3568.7	—	146.00/ 2.39	—	—	—	18.00/ 0.29	30.00/ 0.49
3	180.00/ 2.95	—	177.00/ 2.90	175.00/ 2.87	—	185.00/ 3.03	—	—	—	18.00/ 0.29	30.00/ 0.49
3-1/2	303.00/ 4.97	—	300.00/ 4.92	300.00/ 4.92	—	314.00/ 5.15	—	—	—	—	50.00/ 0.82
4	340.00/ 5.57	—	330.00/ 5.41	330.00/ 5.41	—	345.00/ 5.65	—	—	—	—	50.00/ 0.82

‡ Add suffix **-PVC** to catalog number.