





**NEW GB Xtreme™ Primary Wire**

Tinned copper wire provides maximum protection against corrosion and electrolysis.

- Ultra-flexible (Type 3) stranding.
- Resists salt water, battery acid, oil, gasoline and UV radiation.
- Insulation is heat and abrasion-resistant.
- Packaged in small spools.
- Rated to 600 V and 105 °C (221 °F) maximum.



	Part #	Pkg Qty	Wire Gauge	Length
	AMW-310	1/clam	10 AWG	8 FT
	AMW-312	1/clam	12 AWG	12 FT
	AMW-314	1/clam	14 AWG	18 FT
	AMW-316	1/clam	16 AWG	25 FT
	AMW-318	1/clam	18 AWG	35 FT
	AMW-304	1/clam	14 AWG	18 FT
	AMW-306	1/clam	16 AWG	25 FT
	AMW-308	1/clam	18 AWG	35 FT

	Part #	Pkg Qty	Wire Gauge	Length
	AMW-320	1/clam	10 AWG	8 FT
	AMW-322	1/clam	12 AWG	12 FT
	AMW-324	1/clam	14 AWG	18 FT
	AMW-326	1/clam	16 AWG	25 FT
	AMW-328	1/clam	18 AWG	35 FT
	AMW-330	1/clam	10 AWG	8 FT
	AMW-332	1/clam	12 AWG	12 FT
	AMW-334	1/clam	14 AWG	18 FT
	AMW-336	1/clam	16 AWG	25 FT
	AMW-338	1/clam	18 AWG	35 FT

**NEW Primary Wire**

Manufactured to OEM standards and recommended for repairs or new wiring applications.

- Fine stranding for flexibility.
- 100% copper wire.
- 18-12 AWG.
- Packaged in small coils.
- Rated for 12 volts, insulation operates optimally between the temperatures of -34°C to 90°C (-29°F to 194°F).
- Meets or exceeds S.A.E. specification J1128, Ford M1L56A and Chrysler MS 3450.

	Part #	Pkg Qty	Wire Gauge	Length
	GWB-1212	1/clam	12 AWG	12 FT
	GWB-1420	1/clam	14 AWG	20 FT
	GWB-1625	1/clam	16 AWG	25 FT
	GWB-1835	1/clam	18 AWG	35 FT
	GWG-1212	1/clam	12 AWG	12 FT
	GWG-1420	1/clam	14 AWG	20 FT
	GWG-1625	1/clam	16 AWG	25 FT
	GWG-1835	1/clam	18 AWG	35 FT

	Part #	Pkg Qty	Wire Gauge	Length
	GWR-1212	1/clam	12 AWG	12 FT
	GWR-1420	1/clam	14 AWG	20 FT
	GWR-1625	1/clam	16 AWG	25 FT
	GWR-1835	1/clam	18 AWG	35 FT
	GWW-1212	1/clam	12 AWG	12 FT
	GWW-1420	1/clam	14 AWG	20 FT
	GWW-1625	1/clam	16 AWG	25 FT
	GWW-1835	1/clam	18 AWG	35 FT

TERMINALS & WIRE

