

**IEC Power Devices**  
**Mini Contactors**  
**C-2000**  
**AC 3-Pole, Up to 24 VDC Coil**  
**Nonreversing**  
Line Voltage - 600 VAC Maximum  
HP Ratings AC-3 Duty

**24 VDC PLC Contactors Standard Screw Type Terminals**

Maximum Current @ 460 V (A)	3-Phase HP @60 Hz, 200-208V	3-Phase HP, @60 Hz, 220-240V	3-Phase HP @60 Hz, 460-480V	3-Phase HP @60 Hz, 550-600V	kW @ 50 Hz, 380/415V	1-Phase HP @60 Hz, 115V	1-Phase HP @60 Hz, 230V	Contact Configuration	Coil Wattage	Product Number	List Price GO-10A1
6.0A	1.5	1.5	3	3	2.2	1/3	1	1NO	1.2w	MC0I310ATD	\$50.00
6.0A	1.5	1.5	3	3	2.2	1/3	1	1NC	1.2w	MC0I301ATD	\$50.00
6.0A	1.5	1.5	3	3	2.2	1/3	1	1NO	2w	MC0K310ATD	\$50.00
6.0A	1.5	1.5	3	3	2.2	1/3	1	1NC	2w	MC0K301ATD	\$50.00
9.0A	3	3	5	5	4	1/2	1.5	1NO	1.2w	MC1I310ATD	\$54.00
9.0A	3	3	5	5	4	1/2	1.5	1NC	1.2w	MC1I301ATD	\$54.00
9.0A	3	3	5	5	4	1/2	1.5	1NO	2w	MC1K310ATD	\$54.00
9.0A	3	3	5	5	4	1/2	1.5	1NC	2w	MC1K301ATD	\$54.00

Minimum order is 140 pieces. Packaged in multiples of 10 units. Each product number represents one unit.

Select the Mini-Contactor product number that corresponds to the desired Contactor Rating.

