



Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated
Accessory / separate part type	Shunt trip 120/208/240 V AC

Complementary

Line Rated Current	90 A
Poles description	2P
Breaking capacity	10 kA at: 120/240 V AC 10 kA at: 120 V AC 5 kA at: 60 V DC
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
System Voltage	120 V AC 120/240 V AC 60 V DC
Mounting mode	Unit mount
AWG gauge	AWG 12...AWG 2/0 (aluminium/copper)
Height	4.45 in
Depth	2.95 in
Width	2.25 in

Environment

product certifications	CSA IEC UL listed
------------------------	-------------------------

Offer Sustainability

Not Green Premium product	Not Green Premium product
Will be Compliant on 3Q2014	Will be Compliant on 3Q2014 Will be Compliant on 3Q2014

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.