

- Meets or Exceeds: ASTM B3, ASTM-B8 or ASTM-B787

# BARE COPPER

## Soft Drawn Bare Copper Wire

### APPLICATIONS

- For use in overhead transmission and distribution applications
- For use in grounding applications

### CONDUCTORS

- Solid conductors uncoated copper per ASTM-B3
- Stranded conductors 8 AWG - 2 AWG and 250 MCM - 500 MCM uncoated copper per ASTM-B3 and ASTM-B8
- Stranded conductors 1 AWG - 4/0 AWG - uncoated copper conductors per ASTM-B3 and ASTM-B787

### INDUSTRY STANDARDS

- ASTM-B3
- ASTM-B8
- ASTM-B787

Product Code Number	AWG Size	Class B Strand		Overall Diam. Inches	Approx. lbs./m ft.
		No. of Strands	Diam. Each Inches		
050-2000	8	SOL	.1285	.1285	50
050-2215	6	SOL	.1620	.1620	79
050-2200	6	SOL	.1620	.1620	79
050-2400	4	SOL	.2043	.2043	126
050-2600	2	SOL	.2576	.2576	201
050-4000	8	7	.0486	.146	50
050-4200	6	7	.0612	.184	80
050-4400	4	7	.0772	.232	127
050-4600	2	7	.0974	.292	202
050-5000	1/0	19	.0807, .0591	.360	323
050-5200	2/0	19	.0906, .0663	.404	404
050-5400	3/0	19	.1017, .0745	.454	509
050-5600	4/0	19	.1142, .0836	.510	643

Package Code	D	H	I	J	K
AWG Size	125' spool	200' spool	315' spool	500' spool	1000' reel
8 Solid				X	
6 Solid (050-2200)					X
6 Solid (050-2215)			X		
4 Solid		X		X	X
2 Solid	X				
8 Stranded				X	X
6 Stranded			X		X
4 Stranded		X			X
2 Stranded	X				X
1/0				X	X
2/0				X	X
3/0				X	X
4/0				X	X