



Plate straps are nailed across studs to restrain pipe between studs; installed over utility pipes & electrical wire that pass through framing members to prevent piercing.

- 12 Gauge Steel
- 16 Gauge Steel
- Various Lengths

CAT NO	UPC		SIZE	STD	MSTR	WT/STD	UNIT
PS129	60010	12 Gauge	1-1/2 x 9"	50	50	16.66#	C
PS1212	60012		1-1/2 x 12"	50	50	23.50#	C
PS1218	60014		1-1/2 x 18"	50	50	36.00#	C
PS1224	60016		1-1/2 x 24"	50	50	41.20#	C
PS169	60018	16 Gauge	1-1/2 x 9"	50	50	9.14#	C
PS1612	60020		1-1/2 x 12"	50	50	15.40#	C
PS1618	60022		1-1/2 x 18"	50	50	19.58#	C
PS1624	60024		1-1/2 x 24"	50	50	28.50#	C



UPC Approved (Plumbing Code)

One Hole Straps | PC 5160



One Hole Straps are used to secure cables, tubing, pipe or E.M.T. to a surface

- Zinc Plated Steel (After Fabrication)
- Inverted Rib For Strength
- For E.M.T. / Pipe

CAT NO	UPC	TYPE	SIZE	GAUGE	STD	MSTR	WT/STD	UNIT
TW14	27745	Coaxial	1/4"	18 GA	100	1000	0.57#	C
TW38	27750	BX *	3/8"	18 GA	100	1000	1.15#	C
TW50-1	27700	E.M.T.	1/2"	18 GA	100	1000	2.22#	C
TW75	27705		3/4"	18 GA	100	1000	3.12#	C
TW100	27710		1"	18 GA	100	500	3.45#	C
TW125	27715		1-1/4"	15 GA	100	500	5.49#	C
TW150	27720		1-1/2"	15 GA	50	500	3.86#	C
TW200	27725		2"	13 GA	50	500	7.10#	C
TW250	27726	E.M.T./Pipe	2-1/2"	9 GA	25	100	10.13#	C
TW300	27727		3"	9 GA	25	100	13.38#	C
TW350	27728		3-1/2"	7 GA	25	100	16.61#	C
TW400	27729		4"	7 GA	25	100	19.02#	C
MTW50	27730	E.M.T. Medium Weight	1/2"	14 GA	100	1000	3.62#	C
MTW75	27735		3/4"	14 GA	100	1000	4.17#	C
MTW100	27740		1"	14 GA	100	500	5.45#	C
HW50	27800	Pipe	1/2"	18 GA	100	1000	2.53#	C
HW75	27805		3/4"	18 GA	100	1000	3.19#	C
HW100	27810		1"	14 GA	100	1000	6.66#	C
HW125	27815		1-1/4"	13 GA	50	500	5.49#	C
HW150	27820		1-1/2"	11 GA	50	500	8.36#	C
HW200	27825		2"	11 GA	50	500	10.66#	C
MHW50	27830	Pipe Medium Weight	1/2"	14 GA	100	1000	3.82#	C
MHW75	27835		3/4"	14 GA	100	1000	5.00#	C
MHW100	27840		1"	14 GA	100	1000	6.71#	C

* Accommodates 12-2, 12-3, 10-2, 10-3 BX

