



GREAVES EXCLUSIVE

# POOL and SPA "Jones Bond" system

## CONTINUOUS LOOP BONDING & GROUNDING

Swimming pools / spas, foundation footings, agricultural buildings and other difficult environments

### JONES REBAR CLAMP

Connect grounding electrode conductor to rebar (concrete encased electrode)  
Rugged and compact with no awkward projections - easy coverage in concrete  
Lay-in feature allows continuous-run or termination  
Cast bronze body with stainless steel hardware  
The J32-DB handles a range of rebar sizes and wire sizes  
CSA (C US) certified and UL listed for direct burial in earth or concrete

### Rebar Clamp


NAED NUMBER	CATALOG NUMBER	WIRE RANGE	REBAR SIZE		CTN QTY	EST. SHIPPING	
			#	INCH		WEIGHT (lbs)	UNIT
27101	J 29-DB	6 SOL - #8	3	3/8	50	7.74	CTN
27110	J 30-DB	4 STR - #8 SOL	4	1/2	50	8.49	CTN
27120	J 31-DB	2/0 STR - #6 SOL	5	5/8	25	5.66	CTN
27130	** J 32-DB	4/0 STR - #6 SOL	4,5,6	1/2,5/8,3/4	12	4.18	CTN

J-series clamps are designed for bare rebar only  
Do not use on ground rod, pipe, or epoxy-coated rebar  
Installation torque 150 in-lbs

\*UL listed for #4 STR - #2 STR  
\*\*UL pending



Direct Burial  
Copper wire only



Patent Pending

### BEAVER TOOTH LUG


Use on electrical equipment, pool/spa equipment, conduit bushings, jumper to multiple conduits  
Copper body, stainless steel screw, for use with copper wire only

### Lay-in-Lug

NAED NUMBER	CATALOG NUMBER	WIRE RANGE	BOLT SIZE	CTN QTY	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
27201	BTL 4-DB	#4 -14 AWG	#10	50	3.06	CTN
27202	BTL 4-DBP	#4 -14 AWG	#10	50	3.06	CTN
27205	BTL 414-DB	#4 -14 AWG	1/4	50	3.89	CTN
27206	BTL 414-DBP	#4 -14 AWG	1/4	50	3.89	CTN

DBP is tin-plated for use on aluminum pool structure. Use of oxide-inhibitor is recommended.

Direct Burial  
Copper wire only



### BUGLUGS™


Heavy duty silicon bronze and copper, tin-plated  
For use with copper wire only

### Lay-in-Lug

NAED NUMBER	CATALOG NUMBER	WIRE MAX	MOUNTING BOLT SIZE	CTN QTY	EST. SHIPPING	
					WEIGHT (lbs)	UNIT
70850	BL 6	#6	#10	50	2.92	CTN
70855	BL 4	#4	1/4	50	4.40	CTN
70860	BL 2	#2	1/4	50	6.91	CTN
70865	BL 1/0	1/0	5/16	25	5.27	CTN

Tin-plated for use on aluminum pool structure. Use of oxide-inhibitor is recommended.

Direct Burial  
Copper wire only



Patent Pending

### MESH-BUG™

Use to connect copper conductor to wire mesh  
Copper-alloy bronze construction  
Sizes available for rolled (#10) and heavy (#6) wire mesh  
UL listed for direct burial in earth and concrete

NAED NUMBER	CATALOG NUMBER	MESH/ WIRE SIZE	COPPER COND. RANGE (AWG)	EST. SHIPPING	
				WEIGHT (lbs)	UNIT
10131	A2-DB	#10	#8 -12 AWG	0.03	CTN
10132	A3-DB	#10	#6 SOL - 8 AWG	0.05	CTN
10241	A5-DB	#6, #10	#4 AWG - 8 SOL	0.06	CTN
10251	A8-DB	#2	#2 - 6 AWG	0.11	CTN
10261	A10-DB	#1/0	#1/0 - 4 AWG	0.16	CTN

Direct Burial  
Copper wire only

