

3" (76 mm) Submersible Trash Pump



- Compact, under 12" (300 mm) diameter to easily fit into small areas.
- Self-priming submersible pump can be placed and operated quickly.
- Passes up to 3" (76 mm) solids minimizing pump blockage from debris.
- Can be run dry without damage for longer working life.
- Carry handle with lifting eye makes it easy to transport, move, lift, and lower.
- Locking coupler for discharge hose included.
- Can draw water down to depth of 2-3/4" (70 mm).

SPECIFICATIONS

System	Open- and Closed-Center
Capacity	Up to 500 gpm (1893 lpm) [at 8 gpm (30 lpm) and a 15' (4.5 m) head height]
Intake Port	3.125" (79.4 mm)
Discharge Port	3" (76.2 mm) NPT Female
Trash Diameter	3" (76 mm)
Weight	28 lbs. (11.7 kg)
Height	14.18" (360 mm) over handle
Width	11.87" (301 mm) diameter
Flow Range	7 - 10 gpm (26.5 - 37.9 lpm)
Operating Pressure	0 - 2,000 psi (0 - 138 bar)
Pressure Port Thread	1/2" Male NPTF
Return Port Thread	1/2" Male NPTF

CAT. NO.	UPC NO.	DESCRIPTION
H4635	49334	Hydraulic 3" Trash Pump
49499	49499 A	3" Diameter x 25' Discharge Hose Assembly
F020196K	41778 A	HTMA Female Coupler - 1/2" NPTF internal thread
F020197K	41779 A	HTMA Male Coupler - 1/2" NPTF internal thread

4" (102 mm) Submersible Trash Pump



- No clog, self-priming, abrasion resistant impeller pump.
- Up to 900 gpm (3,407 lpm).
- Replaceable wear plates, carry handle and can be run dry without damage.
- 4" NPT discharge – will pass 3" (76 mm) solids.
- Locking coupler for discharge hose included.
- Can draw water down to depth of 3-1/4" (83 mm).

SPECIFICATIONS

System	Open- and Closed-Center
Capacity	Up to 900 gpm (3,407 lpm) [at 9 gpm (34 lpm) and a 0' (0 m) head height]
Intake Port	4" (102 mm)
Discharge Port	4" (102 mm) NPT Male
Weight	59 lb. (26.7 kg)
Height	15.75" (400 mm)
Width	14.5" (368 mm) diameter
Flow Range	5 - 9 gpm (19 - 34 lpm)
Operating Pressure	0 - 2,000 psi (0 - 138 bar)
Pressure Port Thread	1/2" Male NPTF
Return Port Thread	1/2" Male NPTF

CAT. NO.	UPC NO.	DESCRIPTION
H4670	42192	Submersible Trash Pump
154955	41189 A	4" Diameter x 25' Discharge Hose Assembly
F020196K	41778 A	HTMA Female Coupler - 1/2" NPTF internal thread
F020197K	41779 A	HTMA Male Coupler - 1/2" NPTF internal thread

N = NEW PRODUCT **R** = REPLACEMENT PART **A** = ACCESSORY

USA Tel: 800.435.0786
Fax: 800.451.2632

Canada Tel: 800.435.0786
Fax: 800.524.2853

International Tel: +1.815.397.7070
Fax: +1.815.397.9247