



**120 Volt, 6 watt
240 Volt, 6 watt**



Large pipes




Cut-to-length for wet locations, roof de-icing, and drain lines


WinterGard Wet heating cable, 6 watts/ft

Catalog #	Description	Voltage	Reel Length (ft)
H612050	Box	120	50
H612100	TruckPak*	120	100
H612250	Reel	120	250
H612500	Reel	120	500
H6121000	Reel	120	1000
H622050	Box	240	50
H622100	TruckPak*	240	100
H622250	Reel	240	250
H622500	Reel	240	500
H6221000	Reel	240	1000

**120 Volt, 6 watt
240 Volt, 6 watt**



Preassembled for pipes




Preassembled for roofs

Gardian heating cable, 6 watts/ft

Catalog #	Voltage	Pre-assembled Length (ft)
W51-6P	120	6
W51-12P	120	12
W51-18P	120	18
W51-24P	120	24
W51-50P	120	50
W51-75P	120	75
W51-100P	120	100
W52-6L	240	6
W52-12L	240	12
W52-18L	240	18
W52-24L	240	24

**120 Volt
240 Volt**



Compressor crankcase heating

FreezGard crankcase heater

Catalog #	Voltage	Pre-assembled Length (ft)
CCH-1C	120	4
CCH-2C	240	4

*TruckPak consists of a 100-foot cable reel, two power connections, one splice/tee kit, one roll of application tape, and 10 "Electric Traced" labels.

Note: Use only in ordinary (nonhazardous) areas. Do not expose to any chemicals. In wet areas, use only WinterGard Wet or Gardian.



Warning:

To minimize the danger of fire from sustained electrical arcing if the heating cable is damaged or improperly installed, and to comply with the requirements of Tyco Thermal Controls and national electrical codes, ground-fault equipment protection must be used on each heating cable branch circuit. Arcing may not be stopped by conventional circuit protection.

Note:

This application guide does not take the place of the installation instructions. Carefully follow the installation instructions included in the Raychem accessory kits. Pipes are shown without insulation for illustrative purposes only.

WinterGard Plus		WinterGard Wet		Gardian	
H611050	H621050	H612050	H622050	W51-6P	W52-6L
H611100	H621100	H612100	H622100	W51-12P	W52-12L
H611250	H621250	H612250	H622250	W51-18P	W52-18L
		H612500	H622500	W51-24P	W52-24L
		H6121000	H6221000	W51-50P	
				W51-75P	
				W51-100P	
120	208-240	120	208-240	120	208-240
6	6	6	6	6	6
n/a	n/a	8	8	8	n/a
200	350	200	350	n/a	n/a
n/a	n/a	150	250	n/a	n/a
20	20	20	20	15	15
30	30	30	30	15	15
6	6	9	9	n/a	n/a
150	150	150	150	150	150
Dry area pipes		Dry and wet area pipes, roof and gutter de-icing			Pipes only
(2)	(2)	(2, 3)	(2, 3)	(1, 2, 3)	(2)
(4)	(4)	(4)	(4)	(4)	(4)