



CoverShield
 < Safety Coated Lamps

CoverShield

GENERAL SERVICE
 INCANDESCENT & HEAT LAMPS

Halco
 LIGHTING TECHNOLOGIES

Technical Data

- Sturdy C9 and C-9M staggered-mount filament for rough/vibration service applications
- Silicone or Teflon coating are shatter-resistant and protect lamps from thermal shock
- Brass base

Benefits

- Contains glass shards within lamp's envelope
- Helps offset the risk of contamination or injury and eliminates expense of cleanup

Broad Assortment

- Available in A15, A19, A21, B10, BR30, BR40, PS25, R12, R20 and T10
- 20, 25, 30, 40, 60, 65, 75, 100, 120, 150, 200, 250 and 375 watt
- 1,500 - 5,000 Hours Average Rated Life

Applications

- Food service
- Freezers/Commercial coolers
- Outdoor lighting
- Drop lights
- Construction sites

Safety coated with protective Silicone or Teflon® covering for shatter resistance.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.



where there's light, there's halco®

(800) 677-3334

halcolighting.com

INCANDESCENT

Bulb	Base	Watts	Product Number	Product Code	Description	Pkg Qty	Lumens	Avg. Life	MOL
R12	BA15s	20	1383/CS	1383/CS	S.C. Bayonet	10/1000	-	300	2.60"
A19	Med.	25	101124	A19RS25/CS	Clear	20/120	160	2000	4.25"
⊕ R20	Med.	30	10102	R20FL30/CS	Flood	10/100	140	3000	3.93"
A15	Med.	40	90300	A15CL40/CSTF	Clear Teflon®	20/120	300	3000	3.50"
A15	Med.	40	6146	A15RS40/CS	Clear	20/120	300	1500	3.50"
A19	Med.	40	101125	A19RS40/CS	Clear	20/120	300	2000	4.25"
B10	Med.	40	102148	ETC40/CS	Clear	25/500	280	3000	3.87"
T10	Med.	40	106228	T10CL40/CS	Clear	25/200	280	2500	5.00"
R20	Med.	50	104016	R20FL50/CS	Flood	10/100	210	2000	4.80"
A15	Med.	60	6147	A15RS60/CS	Clear	20/120	500	1500	3.50"
A19	Med.	60	6141	A19RS60/CS	Clear	20/120	500	2000	4.25"
B10	Med.	60	102146	ETC60/CS	Clear	25/500	500	3000	3.87"
BR30	Med.	65	404051	BR30FL65/CS	Flood	1/24	500	5000	5.37"
A19	Med.	75	6142	A19RS75/CS	Clear	20/120	680	2000	4.25"
A19	Med.	100	6143	A19RS100/CS	Clear	20/120	960	2000	4.25"
A21	Med.	100	6041	A21RS100/P5/CS	Clear	12/60	800	5000	5.00"
BR40	Med.	120	404065	BR40FL120/5/CS	Flood	1/24	1200	5000	6.56"
BR40	Med.	125	90320	BR40CL125/1/CSTF	Clear Heat Teflon®	1/12	-	6000	6.56"
A21	Med.	150	6043	A21RS150/P5/CS	Clear	1/60	1300	5000	5.00"
PS25	Med.	150	401345	PS25CL150/P5/CS	Clear	1/60	1300	5000	6.93"
PS25	Med.	200	401347	PS25CL200/P5/CS	Clear	1/60	2000	5000	6.93"
BR40	Med.	250	404066	BR40CL250/1/CSTF	Clear Heat Teflon®	1/12	-	5000	6.56"
R40	Med.	250	404071	R40RED250/10/CSTF	Red Heat Teflon®	1/12	-	5000	6.56"
R40	Med.	375	104050	R40CL375/CSTF	Clear Heat Teflon®	1/12	-	5000	6.56"

* Teflon® is a registered trademark of DuPont Corporation.

⊕ NEW ITEM!