



CoverShield®

General Service
Incandescent & Heat Lamps

Halco
LIGHTING TECHNOLOGIES®

Halco CoverShield® lamps have a protective coating that restricts glass shards, mercury and phosphors within the lamp's envelope in the event of rupture. This coating helps offset the risk of contamination or injury and eliminates expense of cleanup.

Specifications:

- Sturdy C9 and C-9M staggered-mount filament for rough/vibration service applications
- Silicone or high temperature PFA coatings are shatter-resistant and protect lamps from thermal shock
- Brass base
- Available in A15, A19, A21, B10, BR30, BR40, PS25, R12, R20 and T10 shapes
- 20, 25, 30, 40, 60, 65, 75, 100, 120, 150, 200, 250 and 375 wattages
- 1,500 - 6,000 Hours Average Rated Life
- Safety coating is warranted for the rated life of the lamp

- » Shatter-Resistant Lighting
- » Safety coated with protective Silicone or high temperature PFA

Markets:

- Commercial
- Industrial

Applications:

- Food service
- Freezers/Commercial coolers
- Outdoor lighting
- Drop lights
- Construction sites

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at halcolighting.com



General Service Incandescent & Heat Lamps

Catalog Number: _____ Type: _____
 Project: _____
 Comments: _____ Date: _____
 Prepared By: _____

GENERAL SERVICE

Ordering Information

Watt	Base	Product #	Product Code	Description	Lumens	Avg. Rated Life	Pkg. Qty	MOL
A15								
40 Watt	Med.	90300	A15CL40/CSTF	Clear PFA	300	3000	20/120	3.50"
40 Watt	Med.	6146	A15RS40/CS	Clear	300	1500	20/120	3.50"
60 Watt	Med.	6147	A15RS60/CS	Clear	500	1500	20/120	3.50"
A19								
25 Watt	Med.	101124	A19RS25/CS	Clear	160	2000	20/120	4.25"
40 Watt	Med.	101125	A19RS40/CS	Clear	300	2000	20/120	4.25"
60 Watt	Med.	6141	A19RS60/CS	Clear	500	2000	20/120	4.25"
75 Watt	Med.	6142	A19RS75/CS	Clear	680	2000	20/120	4.25"
100 Watt	Med.	6143	A19RS100/CS	Clear	960	2000	20/120	4.25"
A21								
100 Watt	Med.	6041	A21RS100/P5/CS	Clear	-	5000	12/60	5.00"
150 Watt	Med.	6043	A21RS150/P5/CS	Clear	1300	5000	1/60	5.00"
B10								
40 Watt	Med.	102148	ETC40/CS	Clear	370	3000	25/500	3.87"
60 Watt	Med.	102146	ETC60/CS	Clear	650	3000	25/500	3.87"
B30								
65 Watt	Med.	404051	BR30FL65/CS	Flood	580	5000	1/24	5.37"
B40								
120 Watt	Med.	404065	BR40FL120/5/CS	Flood	1200	5000	1/24	6.56"
125 Watt	Med.	90320	BR40CL125/1/CSTF	Clear Heat PFA	-	6000	1/12	6.56"
250 Watt	Med.	404066	BR40CL250/1/CSTF	Clear Heat PFA	-	5000	1/12	6.56"
F15								
60 Watt	Med.	90301	F15CL60/CS	Clear Flame	550	2500	25/250	4.50"
PS25								
150 Watt	Med.	401345	PS25CL150/P5/CS	Clear	1600	5000	1/60	6.93"
200 Watt	Med.	401347	PS25CL200/P5/CS	Clear	2400	5000	1/60	6.93"
R12								
20 Watt	BA15s	1383/CS	1383/CS	S.C. Bayonet	-	300	10/1000	2.60"
R20								
30 Watt	Med.	10102	R20FL30/CS	Flood	140	3000	10/100	3.93"
50 Watt	Med.	104016	R20FL50/CS	Flood	210	2000	10/100	3.93"
R40								
250 Watt	Med.	404071	R40RED250/10/CSTF	Red Heat PFA	-	5000	1/12	6.56"
375 Watt	Med.	104050	R40CL375/CSTF	Clear Heat PFA	-	5000	1/12	6.56"
T10								
40 Watt	Med.	106228	T10CL40/CS	Clear	280	2500	25/200	5.00"