

# Watertight Wiring Devices and Accessories

## Quick Reference Guide



### Watertight Straight Blade Devices

NEMA 4, 4X, 6 and 6P Rated  
IP65, IP66, IP67

Amps	Volts	Nema	Plug		Connector with Cap		Receptacle w/Lift Cover	Listings	
			Yellow	Black*	Yellow	Black*		UL	SR
15A	125V	5-15	14W47H	14W47HBK	15W47H	15W47HBK	60W47H	✓	✓
	250V	6-15	14W49H		15W49H		60W49H	✓	✓
	15A/125V, 10A/250V	Non-NEMA	14W07H		15W07H				✓
20A	125V	5-20	14W33H		15W33H		60W33H	✓	✓
	250V	6-20	14W48H		15W48H		60W48H	✓	✓


\* Other configurations available in black. Consult Factory.



14W33H



15W47H



24W49H

### Watertight Locking Devices

NEMA 4, 4X, 6 and 6P Rated  
IP65, IP66, IP67

Amps	Volts	Nema	Plug		Connector with Cap		Receptacle w/Lift Cover	Listings	
			Yellow	Black*	Yellow	Black*		UL	SR
15A	125V	L5-15	24W47H		25W47H		65W47H	✓	✓
	250V	L6-15	24W49H		25W49H		65W49H	✓	✓
	277VAC	L7-15	24W34H		25W34H		65W34H	✓	✓
20A	125V	L5-20	26W47H		27W47H		67W47H	✓	✓
	250V	L6-20	26W48H		27W48H		67W48H	✓	✓
	277VAC	L7-20	26W49H		27W49H		67W49H	✓	✓
	125/250V	L14-20	26W74H		27W74H		67W74H	✓	✓
	3Ø 250V	L15-20	26W75H	26W75HBK	27W75H	27W75HBK	67W75H	✓	✓
	3Ø 480V	L16-20	26W76H	26W76HBK	27W76H	27W76HBK	67W76H	✓	✓
30A	125/250V	Non-NEMA	26W08H		27W08H		67W08H	✓	✓
	125V	L5-30	28W47H		29W47H		69W47H	✓	✓
	250V	L6-30	28W48H		29W48H		69W48H	✓	✓
	277VAC	L7-30	28W49H		29W49H		69W49H	✓	✓
	125/250V	L14-30	28W74H		29W74H		69W74H	✓	✓
	3Ø 250V	L15-30	28W75H		29W75H		69W75H	✓	✓
	3Ø 480V	L16-30	28W76H		29W76H		69W76H	✓	✓
	3Ø 600V	L17-30	28W77H		29W77H		69W77H	✓	✓
	3ØY 120/208V	L18-30	28W78H		29W78H			✓	✓
	125/250V	Non-NEMA	28W08H		29W08H		69W08H	✓	✓
3ØY 120/208V	Non-NEMA	28W09H		29W09H			✓	✓	

\* Other configurations available in black. Consult Factory.



29W76H



69W76H



6700H



3059H



3090FH

### Weather Protective Lift Cover Assembly

NEMA 3R Rated

Description	Catalog Number	Listings
For use with 15A/20A straight blade or 15A locking receptacle; receptacle not included	6500H	✓
For use with 20A locking receptacle; receptacle not included	6700H	✓
For use with 30A locking receptacle**; receptacle not included	6800H	✓

\*\* When mating with 28W08BRY plug, use 6700BRY.

### Portable Outlet Boxes

NEMA Type 1 Rated

Description	Catalog Number
Portable Outlet Box	3059H
Portable Outlet Box Deep	3099H
Portable Outlet Box with Feed Thru	3090FH
Portable Outlet Box with (2) Duplex Cover Plates	3000H

### Outlet Box Covers

NEMA Type 1 Rated

Description	Cover Plate	Cover Plate with Lift Cover
Outlet Box Lift Cover; Duplex Receptacle	3051H	3056H
Outlet Box Lift Cover; 1.39" Diameter Receptacle	3052H	3057H
Outlet Box Lift Cover; 1.572" Diameter Receptacle	3053H	3058H
Outlet Box Lift Cover; GFCI	3060H	3061H
Outlet Box Coverplate; Blank	3054H	—