

L630C -- Locking Connector Body



Hubbell-Pro locking devices provide a safe disconnect solution between an equipment load and a power source. These devices incorporate a locking interface that is engaged and disengaged simply by rotating the device assuring a safe and reliable electrical connection.

Product Specifications

SELECTSPEC Product Type	Locking Devices
Locking Device Product	Connector Body
Locking Device Rating	30A, 250V
Locking Device Wiring Scheme	2 Pole, 3 Wire Grounding
Locking Device NEMA Configuration	L6-30R
Locking Device Color	Black & White
Locking Device Listings and Approvals	UL Listed, CSA Certified
Features	Nylon Construction, Visible NEMA Ratings, Captive Assembly Screws
Body	Supertough Nylon
Blade/Contact Holder	Impact Modified Nylon
Contacts/Blade Material	High Performance Copper Alloy
Dielectric Voltage	Withstands 3,500V per UL498
Max Working Voltage	600V AC, 250V DC
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Maximum 30 deg C. temperature rise at full rated current after 50 cycles overload at 150% rated current for either AC or DC applications per UL 498
Overload	Minimum 4.8 times rated current for 100 cycles.
Terminal Identification	Terminals identified in accordance with UL 498 (Brass, White, Green).
Terminal Accommodation	#18 to #8 AWG Flexible Cord
Product Identification	Ratings and NEMA identification are permanently marked on device.
Flammability	HB or Better per UL 94 or CSA 22.2 No. 17
Operating Temperatures	Maximum Continuous 60 deg C, minimum -40 deg c. (w/o impact).
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

