



Twist-Lock® Devices

50 Ampere, 125/250, 3Ø 250 Volts and 3Ø 480 Volts AC

3 Pole, 4 Wire Grounding

Plugs, Flanged Inlets, Connector Bodies and Receptacles

IP20
SUITABILITY



50A
125/250V AC
UL/CSA



50A
3Ø 250V AC
UL/CSA




50A
3Ø 480V AC
UL/CSA

Plugs

Description	Cord Dia.	Catalog Number		
Nylon cover, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	CS6365C	CS8365C	CS8165C

Accessories on page B-60.



CS6365C

Flanged Inlets

Description	Catalog Number		
Zinc plated steel casing, thermoset interior.	CS6375	CS8375	CS8175
Zinc plated steel casing, thermoset interior with lift cover.	CS6375M2	-	-
Gray Valox® housing and flange.	HBL6375S	-	-



CS6375

IP20
SUITABILITY



50A
125/250V AC
UL/CSA



50A
3Ø 250V AC
UL/CSA




50A
3Ø 480V AC
UL/CSA

Connector Bodies

Description	Cord Dia.	Catalog Number		
Nylon cover, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	CS6364C	CS8364C	CS8164C

Accessories on page B-60.




CS6375M2


Receptacles

Description	Catalog Number		
Black melamine.	CS6369	CS8369	CS8169

Accessories on page B-60.



CS6364C



CS6369

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

