



2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Nylon Casing, Back Wire Groundingd, White

Product Specifications	
Product Type	 Flanged Receptacles
Standard	NEMA
Amperage	15A
Voltage	125V
Poles and Wires	2 Pole, 3-Wire Grounding
Wiring Method	Back Wired
Hospital Grade ?	No
Receptacle Grade	Heavy Duty Spec Grade
Face Style	Finder Groove
Flange Style	Standard Non-Metallic
Color	 White
NEMA No.	5-15R
Horsepower	0.5
Type	2 Pole, 3 Wire, Grounding
Rating	15A, 125V
Certification	UL Listed, File E2186, Meets NEMA WD-6 requirements Listed to UL Standard 498, Certified to CSA, C22.2, No.

	42
Terminal Screw Material	#8-32 Brass, Multiple Drive
Ground Screw Material	#8-32 Brass, Multiple Drive (Green)
Top Material	Nylon
Base Material	Polycarbonate
Power Contacts Material	.040" (1.0) Brass
Mounting Screw Material	Brass-Nickel Plated
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#14-#10 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 V2.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585173603
Weight in LBs	0.150