

# MOTION SENSORS



## Motion Sensors

Molded bronze housing with double joint, 1/2" mounting stem. Passive infrared detection over 90° coverage area out to 50 feet. 500 watt incandescent switching capacity. Test mode, sensitivity, and burning time duration controls. Sensor consumes 5.4 watts. Internal components protected against moisture for long, reliable life.

### Catalog Number

<b>ZS1</b>	Sensor only, 500 watt incand. capacity, 120V bronze	1.5 lbs
<b>ZS2</b>	Sensor, twin 150 watt lampholders, box and cover, 120V bronze	4.3 lbs

# WALLPACKS



## Perimeter Wallpack

Polycarbonate front provides wide lateral spread and vandal resistance. Lateral coverage is five times the typical 6-10' mounting height. Molded-in bronze finish. Photocontrol units provide dusk-to-dawn energy management. Cast aluminum back housing provides solid mounting to wall or recessed wiring boxes. 1/2" bottom conduit knockout allows surface conduit wiring. For use in wet locations. Lamp included.

### Catalog Number

<b>NRG301B-PC</b>	50 watt HPS, 120V, photocontrol, bronze	5 lbs
<b>NRG307B-PC</b>	70 watt HPS, 120V, photocontrol, bronze	5 lbs
<b>NRG304B-PC</b>	42 watt FLU, 120V, photocontrol, bronze	6 lbs



## Compact Refractor Wallpack

Cast aluminum housing and door with glass refractor on metal halide units. Cast aluminum housing and polycarbonate refractor on vandal-resistant HPS units. Coverage is four times the 8-12' typical mounting height. 1/2" conduit hubs allow surface wiring and field installations of photocontrols. Back hub mounts to standard 4" recessed outlet boxes. Dark bronze finish. Designed for use in wet locations. Lamp incl.

### Catalog Number

<b>WGH70H</b>	70 watt MH, 120V, glass refractor, bronze	9 lbs
<b>WGH100H</b>	100 watt MH, 120V, glass refractor, bronze	10 lbs
<b>WPH70S</b>	70 watt HPS, 120V, polycarbonate refractor, bronze	9 lbs
<b>WPH100S</b>	100 watt HPS, 120V, polycarbonate refractor, bronze	9 lbs



## Mid-size Refractor Wallpack

Cast aluminum housing and door for rugged mounting and protection of internal components. Non-yellowing glass refractor with coverage of four times mounting height laterally and two mounting heights forward. Typical mounting height is 12-15'. 1/2" conduit hubs on sides for surface conduit and top hub allows field installation of photocontrol. Back hub allows wiring access to recessed wiring boxes. Dark bronze finish. For use in wet locations. Lamp included.

### Catalog Number

<b>WGH175H</b>	175 watt MH, 120, 208, 240, 277V, bronze	19 lbs
<b>WGH150S</b>	150 watt HPS, 120, 208, 240, 277V, bronze	18 lbs



## Large Refractor Wallpack

Cast aluminum housing and door with protective dark bronze powder paint for lasting appearance. Glass refractor spreads output for coverage four times laterally and two times forward of typical 18-25' mounting height. 1/2" conduit hubs on side allow surface conduit wiring. Top hub allows location for field installed photocontrol. Back hub provides wiring access to recessed wiring boxes. For use in wet locations. Lamp included.

### Catalog Number

<b>WGH250H</b>	250 watt MH, 120, 208, 240, 277V, bronze	34 lbs
<b>WGH400H</b>	400 watt MH, 120, 208, 240, 277V, bronze	37 lbs
<b>WGH250S</b>	250 watt HPS, 120, 208, 240, 277V, bronze	36 lbs
<b>WGH400S</b>	400 watt HPS, 120, 208, 240, 277V, bronze	40 lbs



## Full Cutoff Wallpacks

Two sizes for total shielding at various mounting heights. Cast aluminum construction with stippled glass lens for lamp diffusion. Full cutoff shielding for environmentally-friendly distribution. Lateral coverage is three times typical mounting height of 8-15". 1/2" hubs allow surface conduit wiring or access to wiring boxes. Top hub allows easy field installation of photocontrol. Dark bronze finish. For use in wet locations. Lamp included.

### Catalog Number

#### Compact Series

<b>WGC50H</b>	50 watt MH, 120, 277V, bronze	10 lbs
<b>WGC70H</b>	70 watt MH, 120, 208, 240, 277V, bronze	11 lbs
<b>WGC100H</b>	100 watt MH, 120, 208, 240, 277V, bronze	12 lbs
<b>WGC100S</b>	100 watt HPS, 120, 208, 240, 277V, bronze	12 lbs

#### Mid-Size Series

<b>WGC175H</b>	175 watt MH, 120, 208, 240, 277V, bronze	19 lbs
<b>WGC150S</b>	150 watt HPS, 120, 208, 240, 277V, bronze	18 lbs