


KT

Grommets, small, single



1.1

IP54 IP66 IP68



Product Description

Cable grommets KT small are used with the cable entry frames & cord grips of product groups 1.11 & 1.12.

The model range KT small is designed for cable diameters from 1 to 17 mm.

Assembly Note

When installing the grommets, the flat side should be facing the middle of the frame. This allows the flat sides of adjacent grommets to match up and provide a secure seal.

Description	Type	Order No gray	Order No black	Clamping range	PU	
	BTK	41251	41351	Blank grommet	10	
	KT 1	39941	39943	1 - 2 mm / 0.039 - 0.079 "	10	
	KT 2	39934	41302	2 - 3 mm / 0.079 - 0.118 "	10	
	KT 3	41203	41303	3 - 4 mm / 0.118 - 0.157 "	10	
	KT 4	41204	41304	4 - 5 mm / 0.157 - 0.197 "	10	
	KT 5	41205	41305	5 - 6 mm / 0.197 - 0.236 "	10	
	KT 6	41206	41306	6 - 7 mm / 0.236 - 0.276 "	10	
	KT 7	41207	41307	7 - 8 mm / 0.276 - 0.315 "	10	
	KT 8	41208	41308	8 - 9 mm / 0.315 - 0.354 "	10	
	KT 9	41209	41309	9 - 10 mm / 0.354 - 0.394 "	10	
	KT 10	41210	41310	10 - 11 mm / 0.394 - 0.433 "	10	
	KT 11	41211	41311	11 - 12 mm / 0.433 - 0.472 "	10	
	KT 12	41212	41312	12 - 13 mm / 0.472 - 0.511 "	10	
	KT 13	41213	41313	13 - 14 mm / 0.511 - 0.551 "	10	
	KT 14	41214	41314	14 - 15 mm / 0.551 - 0.591 "	10	
	KT 15	41215	41315	15 - 16 mm / 0.591 - 0.63 "	10	
		KTs 16	39901	39912	16 mm / 0.63 "	10
		KTs 17	39900	39913	17 mm / 0.669 "	10

*Only valid for gray product types

KT

Grommets, small, multi & Special Grommets



IP54

1.1

Description	Type	Order No gray	Order No black	Clamping range	PU	
	KT 2 x	KT 2 1	39942	39944	2x ø 1 mm / 0.003 "	10
		KT 2 2	39935	39936	2x ø 2 mm / 0.079 "	10
		KT 2 3	39939	39940	2x ø 3 mm / 0.118 "	10
		KT 2 4	39906	39907	2x ø 4 mm / 0.157 "	10
		KT 2 5	41200	39904	2x ø 5 mm / 0.197 "	10
		KT 2 6	41201	39905	2x ø 6 mm / 0.236 "	10
		KT 2 7	41202	39916	2x ø 7 mm / 0.276 "	10
		KT 2 8	39917	39918	2x ø 8 mm / 0.315 "	10
	KT 4 x	KT 4 2	39937	39938	4x ø 2 mm / 0.079 "	10
		KT 4 3	39914	39915	4x ø 3 mm / 0.118 "	10
		KT 4 4	39909	39911	4x ø 4 mm / 0.157 "	10
		KT 4 5	39908	39910	4x ø 5 mm / 0.197 "	10
		KT 4 6	39932	39933	4x ø 6 mm / 0.236 "	10
		KT ASI	KT-ASI	39902	39903	1 ASI-cable
		KT-ASI2 rl	39922	39924	2 ASI-cables	10
		KT-ASI2 ll	39921	39923	2 ASI-cables	10
	KT oval	KT oval	39930	-	approx. 8 x 4 mm / 0.315 x 0.157 "	10
	KT S1	KT S1	39931	-		10
	KT tele	KT tele	39929	-	Telephone cable	10
		KT tele1	41257	-	Data cable RJ12	10
		KT tele2	41258	-	Data cable RJ10 / RJ45	10

Specifications KT gray

Material Elastomer
Flame class UL94-Vo
IP rating KT round, single: up to IP66/IP68
 KT round, multi: IP54
 KT special, multi: IP54
UL type rating up to UL type 4X (acc. to UL 50E)
Operating temperature - 40°C to + 100°C (static)
 - 40°F to + 212°F (static)
Properties Halogen-free, silicone-free

Specifications KT black

Material Elastomer
Flame class UL94-HB
IP rating KT round, single: up to IP66/IP68
 KT round, multi: IP54
 KT special, multi: IP54
Operating temperature - 30°C to + 90°C (static)
 - 22°F to + 194°F (static)
Properties Higher chemical resistance

Accessories

ST Plugs 53

*Only valid for gray product types