

## 900 Series Medium Duty

This family of polyester blocks is ideal for high temperature applications. The rugged material withstands temperatures up to 302°F (150°C)

- Three contact styles cover broad wire range – accept single wire or combinations from 22 AWG to 8 AWG solid or stranded
- Rated at 15A to 50A per circuit
- Flat base models mount directly to surfaces; dovetail base models mount on stranded channel
- Only one end section needed per block assembly
- Readily identifiable circuits - write directly on matte surface of block
- Sections snap-fit with Heavy Duty, Intermediate Heavy Duty and Fuse blocks



### Specifications

**Center-to-Center Spacing:** .375 in.

**Voltage Rating:** 600 Volt max., Current: 50 Amp max.

**Ampacity:** #8 - #22 AWG

Catalog Number	921	0921	924	0924	925	0925	930	0930
<b>Mounting Style</b>	Direct Mount (Flat Base)	Channel Mount (Dovetail Base)	Direct Mount (Flat Base)	Channel Mount (Dovetail Base)	Direct Mount (Flat Base)	Channel Mount (Dovetail Base)	End Section (Direct Mount)	End Section (Channel Mount)
<b>Ampacity</b>	15A		50A		30A		—	—
<b>Contact Type</b>	Strap Screw		Tubular Screw		Tubular Clamp		—	—
<b>Screw Type</b>	6-32 Combo Head		10-32 Combo Head		10-32 Combo Head		—	—
<b>Screw Torque</b>	12 in./lbs.		8 in./lbs.		8 in./lbs.		—	—
<b>Wire Range (AWG)</b>	#14 to #22		#8 to #22		#10 to #22		—	—

<b>Housing Material</b>	Polyester (gray)
<b>Contact Material</b>	Copper Alloy, Zinc Plated
<b>Screw Material</b>	Steel, Zinc Plated
<b>Maximum Service Temperature</b>	150°C (302°F)
<b>Flammability</b>	UL94V-0 Rated



WIRE RANGE: Solid or Stranded

**Strap Screw**

1 #22 to 1 #14 AWG

**Tubular Screw**

1 #8 AWG, 1 #10 AWG, 1 to 3 #12 AWG, 1 to 4 #14 AWG, 1 to 4 #16 AWG, 1 to 5 #18 AWG, 1 to 10 #22 AWG

**Tubular Clamp**

1 #10 AWG, 1 or 2 #12 AWG, 1 to 3 #14 AWG, 1 to 4 #16 AWG, 1 to 5 #18 AWG, 1 to 10 #22 AWG

Terminal Blocks