

# Aculux™ 7" Aperture PAR38

## Adjustable/Downlight Series

Recessed 0-45° adjustable housing for accent, task or downlighting from higher flat or sloped ceiling mounting heights. 120V PAR38 halogen lamp produces spot or flood patterns for medium to high light levels. Features industry exclusive 45° adjustment and 361° rotation.

## Accessories

*Bar Hangers For TC973*

**HB-1** Real Nail bar hangers (set of 2).

**HB-26** 26" C-Channel bar hangers (set of 2).

**HB-50** 50" C-Channel bar hangers (set of 2).

**LB-27** 27" Linear bar hangers (set of 2).

## PAR38 Halogen Adjustable/Downlight Housings


**Air-LOC**



### IC73

Energy-efficient, Air-Loc® rated housing for use in direct contact with insulation. Removable cover allows top access for relamping from above.

Housing dimensions:  
21½" L x 13⅝" W x 11⅞" H  
Ceiling cutout: 8⅞"




### TC973

Requires 3" spacing from insulation. Use with optional HB-1 Residential Bar Hanger Conversion Kit for Joist Construction. Removable cover allows top access for relamping from above.

Optional bar hangers available are listed above.

Housing dimensions:  
21⅞" L x 13⅝" W x 11⅞" H  
Ceiling cutout: 8⅞"



## 7" Aperture PAR38 Trims

### Adjustable Trims



#### Angle-Cut Cone

738B-WH Black Alzak®  
738C-WH Clear Alzak®  
738G-WH Gold Alzak®  
738HZ-WH Haze  
738WHZ-WH Wheat Haze  
IC: 100W PAR38  
TC: 250W PAR38  
7" Aperture

### Downlight Trims



#### Deep Downlight Cone

727B-WH Black Alzak®  
727C-WH Clear Alzak®  
727G-WH Gold Alzak®  
727HZ-WH Haze  
727WHZ-WH Wheat Haze  
IC: 120W PAR38, 120W BR40  
TC: 250W PAR38, 120W BR40  
7" Aperture