

L8515-100

Pulling Grip, 1.00-1.50"

Pulling, Single Eye Cable Grip, Light Duty Single Eye, 1.00-1.50", Galv- Breakload is 7,840 LB



Representative image shown

UPC Code : 078477213711

Country Of Origin : India

- Leviton wire mesh grips are built tough to provide the strength, reliability, and gripping force required for today's demanding wire mesh applications
- Pulling grips are reusable devices for pulling bare conductors, insulated wires, synthetic rope, wire rope, and fiber optic cable
- All pulling grip designs are fully tested to meet published break ratings without slipping

Technical Information

Material Specifications

Mesh Material : Galvanized

Mechanical Specifications

Approx. Break Strength : 7840 lbs (3556 kgs)

Bale Length : 4 in (101.6 mm)

Cable Range : 1.00 - 1.50 in (25.40 - 38.10 mm)

Duty : Light

Eye Type : Single

Mesh Length : 24 in (609.6 mm)

Mesh Style : Closed

Weave : Single Weave

Workload Safety Factor (lbs) : 2613 lbs @ 3:1 (1185 kgs @ 3:1)

Product Features

Device Type : Pulling Grip

Warranty

Warranty : 1-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:		CATALOG NUMBERS:	
<input type="text"/>		<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

